

## Colossal 1200 OPAL

COLOSSAL 1200mm 940 OPAL DIR WHITE SSC  
2071300



### Product features

- 1200mm diameter circular architectural luminaire, can be surface mounted or suspended. Powder coated aluminium housing (RAL9016) with polycarbonate opal diffuser. Direct light distribution, 18745lm luminous flux, 153.6W system power, 122lm/W luminaire efficacy. Sylsmart Standalone enabled. Colour rendering index Ra >90, 4000K Neutral White LED, chromaticity tolerance of 3-step MacAdam ellipse. IP40/IP20, IK03. 450mA drive current. Electrical protection Class1, 220-240V. Reported lifetime 66k hours L90B10.



### PRODUCT OVERVIEW

|                                 |                                        |
|---------------------------------|----------------------------------------|
| Product name                    | COLOSSAL 1200mm 940 OPAL DIR WHITE SSC |
| Technology                      | LED (3 SDCM)                           |
| Cap/Base                        | N/A                                    |
| Housing                         | Aluminium                              |
| Mount                           | Ceiling surface mounting               |
| General application             | Hospitality, Office                    |
| ETIM Class                      | EC002892                               |
| Warranty                        | 5 years                                |
| Fixture luminous flux (lm)      | 18745                                  |
| Luminaire efficacy (lm/W)       | 122                                    |
| Colour temperature (K)          | 4000                                   |
| Colour Code                     | 940                                    |
| Light colour                    | Neutral White                          |
| CRI (Ra)                        | 90                                     |
| Colour Variation Initial (SDCM) | SDCM3                                  |
| Glare control                   | < 22                                   |
| Photobiological Risk Group      | RG0                                    |
| Total power consumption (W)     | 153.6                                  |
| Electrical protection           | Class I                                |
| Control gear type               | LED driver constant current            |
| Dimmable                        | Yes                                    |
| Dimming method                  | SylSmart SSC                           |
| LED Flickering Rate             | Ultra low (5% or less)                 |
| Housing colour                  | RAL 9016 - Traffic white / Bezel       |
| IP rating                       | IP40/20                                |
| IK rating                       | IK07                                   |
| Product EAN number              | 5025768713004                          |

### DATA TABLE

#### General data

|              |                                        |
|--------------|----------------------------------------|
| Product name | COLOSSAL 1200mm 940 OPAL DIR WHITE SSC |
|--------------|----------------------------------------|

## Colossal 1200 OPAL

*COLOSSAL 1200mm 940 OPAL DIR WHITE SSC*  
2071300

|                                  |                          |
|----------------------------------|--------------------------|
| Technology                       | LED (3 SDCM)             |
| Cap/Base                         | N/A                      |
| Housing                          | Aluminium                |
| Mount                            | Ceiling surface mounting |
| General application              | Hospitality, Office      |
| Operating temperature range (°C) | 5°C...+25°C              |
| ETIM Class                       | EC002892                 |
| Warranty                         | 5 years                  |

### Optical data

|                                 |               |
|---------------------------------|---------------|
| Fixture luminous flux (lm)      | 18745         |
| Luminaire efficacy (lm/W)       | 122           |
| Colour temperature (K)          | 4000          |
| Colour Code                     | 940           |
| Light colour                    | Neutral White |
| CRI (Ra)                        | 90            |
| Colour Variation Initial (SDCM) | SDCM3         |
| Distribution type               | Symmetric     |
| Glare control                   | < 22          |
| Photobiological Risk Group      | RG0           |

### Electrical data

|                                                                |                                |
|----------------------------------------------------------------|--------------------------------|
| Total power consumption (W)                                    | 153.6                          |
| Current (A)                                                    | 450                            |
| Primary Supply/Product voltage - min (V)                       | 220                            |
| Primary Supply/Product voltage - max (V)                       | 240                            |
| Lamp power factor                                              | 0.95                           |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x % | 10                             |
| Electrical protection                                          | Class I                        |
| Control gear required                                          | No                             |
| Control gear type                                              | LED driver constant current    |
| Dimmable                                                       | Yes                            |
| Dimming method                                                 | SylSmart SSC                   |
| Drive current (mA)                                             | 450                            |
| Inrush Current (A)                                             | 25                             |
| Inrush Duration (µs)                                           | 280                            |
| Glow Wire Test (°C)                                            | 650                            |
| Energy Efficiency Class (A->G) of contained light source       | C, C(more than 1 Light Source) |
| Nominal Frequency (Hz)                                         | 50/60Hz                        |
| LED Flickering Rate                                            | Ultra low (5% or less)         |
| Max. products per 10A C Breaker                                | 24                             |
| Max. products per 13A C Breaker                                | 31                             |
| Max. products per 16A C Breaker                                | 40                             |
| Max. products per 20A C Breaker                                | 49                             |
| Max. products per 10A B Breaker                                | 13                             |
| Max. products per 16A B Breaker                                | 24                             |
| Max. products per 20A B Breaker                                | 30                             |

## Colossal 1200 OPAL

COLOSSAL 1200mm 940 OPAL DIR WHITE SSC  
2071300

|                                                 |     |
|-------------------------------------------------|-----|
| Connectable conductor cross section - Min (mm²) | 1.5 |
| Connectable conductor cross section - Max (mm²) | 2.5 |

### Lifetime data

|                  |        |
|------------------|--------|
| Lifespan L70 B50 | 170000 |
| Lifespan L80 B20 | 145000 |
| Lifespan L90 B10 | 66000  |

### Physical data

|                               |                                  |
|-------------------------------|----------------------------------|
| Housing colour                | RAL 9016 - Traffic white / Bezel |
| IP rating                     | IP40/20                          |
| IK rating                     | IK07                             |
| Diffuser finish               | Opal                             |
| Diffuser material             | PC Polycarbonate                 |
| Nominal Product Height (mm)   | 93                               |
| Nominal Product Diameter (mm) | 1168                             |
| Weight (kg)                   | 23.0                             |



### Packaging

|                                       |                |
|---------------------------------------|----------------|
| Single packaging type                 | Carton         |
| Product EAN number                    | 5025768713004  |
| Packaging single length / height (cm) | 14.0           |
| Packaging single width (cm)           | 123.0          |
| Packaging single depth (cm)           | 123.0          |
| DUN14 (outer)                         | 05025768713004 |
| Units per outer package               | 1              |
| Packaging outer length / height (cm)  | 14.0           |
| Packaging outer width (cm)            | 123.0          |
| Packaging outer depth (cm)            | 123.0          |

### Safety data

|                                  |      |
|----------------------------------|------|
| Optimal operating condition (°C) | 5-25 |
|----------------------------------|------|

## PHOTOMETRY



## Colossal 1200 OPAL

*COLOSSAL 1200mm 940 OPAL DIR WHITE SSC*  
2071300

### TECHNICAL DRAWINGS

---

