

Inverto Pendant

Inverto Pend Rmt WW 1-10v Silver

3080127

Image not found.

Product features

- Pendant luminaire with remote driver, wire to base with pluggable connection for easy installation, suitable for looping, switchable driver, silver coloured aluminium housing, 1,566lm, 16W, 98lm/W, 3000K, 350mA , CRI:80, 40° beam Angle, 1-10V dimmable, IP20, IK07, lifespan: 60,000hrs (L80:B20), 18.50x29.6x11.5mm.

PRODUCT OVERVIEW

|                             |                                  |
|-----------------------------|----------------------------------|
| Product name                | Inverto Pend Rmt WW 1-10v Silver |
| Technology                  | LED                              |
| Cap/Base                    | N/A                              |
| Housing                     | Aluminium                        |
| Mount                       | Pendant surface                  |
| Environment                 | Internal                         |
| General application         | Hospitality                      |
| ETIM Class                  | EC001743                         |
| Warranty                    | 5 years                          |
| Fixture luminous flux (lm)  | 1566                             |
| Luminaire efficacy (lm/W)   | 98                               |
| LOR (%)                     | 100                              |
| Colour temperature (K)      | 3000                             |
| Light colour                | Warm White                       |
| CRI (Ra)                    | 80                               |
| Colour Consistency (SDCM)   | 3                                |
| Beam Angle (°)              | 40                               |
| Photobiological Risk Group  | RG1                              |
| Total power consumption (W) | 16                               |
| Electrical protection       | Class II                         |
| Control gear type           | Electronic ballast               |
| Dimmable                    | Yes                              |
| Dimming method              | 1-10V (Analogue)                 |
| Minimum dimming level (%)   | 5                                |
| Housing colour              | RAL 9022 - Pearl light grey      |
| IP rating                   | IP20                             |
| IK rating                   | IK07                             |
| Product EAN number          | 8711971801276                    |

DATA TABLE

|              |                                  |
|--------------|----------------------------------|
| General data |                                  |
| Product name | Inverto Pend Rmt WW 1-10v Silver |
| Technology   | LED                              |
| Cap/Base     | N/A                              |
| Housing      | Aluminium                        |

## Inverto Pendant

*Inverto Pend Rmt WW 1-10v Silver*

3080127

|                                         |                 |
|-----------------------------------------|-----------------|
| Mount                                   | Pendant surface |
| Environment                             | Internal        |
| General application                     | Hospitality     |
| Operating temperature range (°C)        | -25°C...+25°C   |
| Performance ambient temperature Tq (°C) | 25              |
| ETIM Class                              | EC001743        |
| Warranty                                | 5 years         |

### Optical data

|                            |            |
|----------------------------|------------|
| Fixture luminous flux (lm) | 1566       |
| Luminaire efficacy (lm/W)  | 98         |
| LOR (%)                    | 100        |
| Colour temperature (K)     | 3000       |
| Light colour               | Warm White |
| CRI (Ra)                   | 80         |
| Colour Consistency (SDCM)  | 3          |
| Adjustable chromaticity    | N          |
| Beam Angle (°)             | 40         |
| Photobiological Risk Group | RG1        |

### Electrical data

|                                                          |                    |
|----------------------------------------------------------|--------------------|
| Total power consumption (W)                              | 16                 |
| Primary Supply/Product voltage - min (V)                 | 220                |
| Primary Supply/Product voltage - max (V)                 | 240                |
| Electrical protection                                    | Class II           |
| Control gear type                                        | Electronic ballast |
| Dimmable                                                 | Yes                |
| Dimming method                                           | 1-10V (Analogue)   |
| Minimum dimming level (%)                                | 5                  |
| Drive current (mA)                                       | 350                |
| Inrush Current (A)                                       | 45                 |
| Inrush Duration (µs)                                     | 20                 |
| Energy Efficiency Class (A->G) of contained light source | D                  |
| Nominal Frequency (Hz)                                   | 50/60Hz            |
| Max. products per 10A C Breaker                          | 50                 |
| Max. products per 16A C Breaker                          | 80                 |

### Lifetime data

|                  |       |
|------------------|-------|
| Lifespan L70 B50 | 60000 |
| Lifespan L80 B20 | 60000 |
| Lifespan L90 B10 | 56100 |

### Physical data

|                 |                             |
|-----------------|-----------------------------|
| Housing colour  | RAL 9022 - Pearl light grey |
| IP rating       | IP20                        |
| IK rating       | IK07                        |
| Diffuser finish | Transparent                 |

## Inverto Pendant

*Inverto Pend Rmt WW 1-10v Silver*

3080127

|                             |       |
|-----------------------------|-------|
| Diffuser material           | Glass |
| Nominal Product Length (mm) | 110   |
| Nominal Product Width (mm)  | 110   |
| Nominal Product Height (mm) | 110   |
| Weight (kg)                 | 1.429 |

### Packaging

|                                       |                |
|---------------------------------------|----------------|
| Single packaging type                 | Carton         |
| Product EAN number                    | 8711971801276  |
| Packaging single length / height (cm) | 18.5           |
| Packaging single width (cm)           | 29.6           |
| Packaging single depth (cm)           | 11.5           |
| DUN14 (outer)                         | 08711971801276 |
| Units per outer package               | 1              |
| Packaging outer length / height (cm)  | 18.5           |
| Packaging outer width (cm)            | 29.6           |
| Packaging outer depth (cm)            | 11.5           |

### Safety data

|                                  |        |
|----------------------------------|--------|
| Optimal operating condition (°C) | -25-25 |
|----------------------------------|--------|

## PHOTOMETRY

---

## TECHNICAL DRAWINGS

---