

Inverto Surface Mounted
Inverto Surface WW Eb White
3081134

Image not found.

Product features

- Surface Ceiling mounted luminaire, wire to base with pluggable connection for easy installation, suitable for looping, white coloured aluminium housing, 1,566lm, 16W, 98lm/W , 3000K, 350mA , CRI:80, 40° beam Angle, non-dimmable, IP65, IK07, lifespan: 60,000hrs (L80:B20), 110 x 110 x 162 mm.

PRODUCT OVERVIEW

Product name	Inverto Surface WW Eb White
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling surface mounting
Environment	Internal/External
General application	Hospitality
ETIM Class	EC002892
E-number FI	4579340
Warranty	5 years
Fixture luminous flux (lm)	1566
Luminaire efficacy (lm/W)	98
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Beam Angle (°)	40
Photobiological Risk Group	RG1
Total power consumption (W)	16
Electrical protection	Class II
Control gear type	Electronic ballast
Dimmable	No
Dimming method	N/A
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP65
IK rating	IK07
Product EAN number	8711971811343

DATA TABLE

General data

Product name	Inverto Surface WW Eb White
Technology	LED
Cap/Base	N/A
Housing	Aluminium

Inverto Surface Mounted

Inverto Surface WW Eb White

3081134

Mount	Ceiling surface mounting
Environment	Internal/External
General application	Hospitality
Operating temperature range (°C)	-25°C...+25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
E-number FI	4579340
Warranty	5 years

Optical data

Fixture luminous flux (lm)	1566
Luminaire efficacy (lm/W)	98
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Beam Angle (°)	40
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	16
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.95
Electrical protection	Class II
Control gear type	Electronic ballast
Dimmable	No
Dimming method	N/A
Drive current (mA)	350
Inrush Current (A)	10
Inrush Duration (µs)	152
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	75
Max. products per 13A C Breaker	91
Max. products per 16A C Breaker	106
Max. products per 20A C Breaker	126
Max. products per 10A B Breaker	45
Max. products per 13A B Breaker	55
Max. products per 16A B Breaker	64
Max. products per 20A B Breaker	76

Lifetime data

Lifespan L70 B50	60000
Lifespan L80 B20	60000

Inverto Surface Mounted

Inverto Surface WW Eb White

3081134

Lifespan L90 B10	56100
------------------	-------

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP65
IK rating	IK07
Diffuser finish	Transparent
Diffuser material	Glass
Nominal Product Length (mm)	110
Nominal Product Width (mm)	110
Nominal Product Height (mm)	162
Weight (kg)	1.479

Packaging

Single packaging type	Carton
Product EAN number	8711971811343
Packaging single length / height (cm)	18.5
Packaging single width (cm)	24.5
Packaging single depth (cm)	11.5
DUN14 (outer)	08711971811343
Units per outer package	1
Packaging outer length / height (cm)	18.5
Packaging outer width (cm)	24.5
Packaging outer depth (cm)	11.5

Safety data

Optimal operating condition (°C)	-25-25
----------------------------------	--------

PHOTOMETRY

TECHNICAL DRAWINGS