


Resisto HE
Resisto 1500 HE IP66 7100lm 840 EM
0010272



Product features

- Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform lit appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time. 7100lm; 50W; 142lm/W; 4000K; SDCM<3; non dimmable; CRI80; IP66; IK08; Class I; 69,000hrs (L80B20) lifespan; 1500mm x 89mm x 88mm; D-mark; 3-hour maintained emergency batteries.




PRODUCT OVERVIEW

Product name	Resisto 1500 HE IP66 7100lm 840 EM
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Suspended, Wall surface mounted
General application	Logistics & Industry
ETIM Class	EC002892
Warranty	5 years
Fixture luminous flux (lm)	7100
Luminaire efficacy (lm/W)	142
Colour temperature (K)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Beam Angle (°)	110
Glare control	< 25
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	760
Luminous flux (emergency) (lm)	760
Total power consumption (W)	50
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Ultra low (5% or less)
Housing colour	Grey
IP rating	IP66
IK rating	IK08
Product EAN number	5410288102726


PHOTOMETRY

Resisto HE
Resisto 1500 HE IP66 7100lm 840 EM
0010272

0.5	1.25 1.39	E(0°) E(C90) E(C270)	9470 9147 8481
1.0	2.51 2.77	E(0°) E(C90) E(C270)	2368 2301 2177
1.5	3.76 4.16	E(0°) E(C90) E(C270)	1552 1501 1395
2.0	5.01 5.55	E(0°) E(C90) E(C270)	902 874 816
2.5	6.26 6.93	E(0°) E(C90) E(C270)	579 561 528
3.0	7.52 8.32	E(0°) E(C90) E(C270)	383 372 352
Distance [m]		Cone diameter [m]	
		Illuminance [lx]	
		C90 - C180 (Half beam angle: 105.4°)	
		C90 - C270 (Half beam angle: 102.8°)	



0.5	1.37 1.42	E(0°) E(C90) E(C270)	978 939 869
1.0	2.74 2.85	E(0°) E(C90) E(C270)	244 235 218
1.5	4.11 4.27	E(0°) E(C90) E(C270)	155 150 139
2.0	5.49 5.81	E(0°) E(C90) E(C270)	91 87 81
2.5	6.86 7.27	E(0°) E(C90) E(C270)	59 56 52
3.0	8.23 8.41	E(0°) E(C90) E(C270)	37 35 33
Distance [m]		Cone diameter [m]	
		Illuminance [lx]	
		C90 - C180 (Half beam angle: 108.0°)	
		C90 - C270 (Half beam angle: 107.8°)	



TECHNICAL DRAWINGS

