

ToLEDo NEOS T8 CCG and AC

ToLEDo T8 V4 2FT 900LM 840 25K 0029300

Product features

Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lampsOmnidirectional uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubesLumen output - 900lmHigh lumen efficacy - 100 lm/WSwitching cycles - 100,000XAverage rated life 25,000 hoursLamp length - 600mmWide beam angleSuitable for general illumination in offices, supermarkets, department stores, parking lotsSuitable for operation with electromagnetic gears/CCG and direct mains operation (220-240V)2-Year warranty










PRODUCT OVERVIEW

| Product name | ToLEDo T8 V4 2FT 900LM 840 25K |
|---------------------------------|---|
| Technology | LED |
| Watt (Rated) (W) | 9 |
| Lamp shape | Tube, double-ended |
| Туре | LED exchangeable |
| Cap/Base | G13 |
| Lamp finish | Opal |
| Fixture rating | Open |
| General application | Education, Logistics & Industry, Office, Residential & Consumer |
| ETIM Class | EC001959 |
| E-number FI | 4941319 |
| Warranty | 2 years |
| Luminous flux (lm) | 900 |
| Colour temperature (K) | 4000 |
| Light colour | Cool White |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM6 |
| Beam Angle (°) | 180 |
| Photobiological Risk Group | RG0 |
| Wattage (W) | 9 |
| Dimmable | No |
| Average life (Nominal) (h) | 25000 |
| IP rating | IP20 |
| Product EAN number | 5410288293004 |

PHOTOMETRY



ToLEDo NEOS T8 CCG and AC ToLEDo T8 V4 2FT 900LM 840 25K 0029300



TECHNICAL DRAWINGS

