


ToLEDo NEOS T8 CCG and AC  
ToLEDo T8 V4 5FT 2300LM 840 25K  
0029304



Product features

- Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lampsOmni-directional uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubesLumen output - 2300lmHigh lumen efficacy - 105 lm/WSwitching cycles - 100,000XAverage rated life 25,000 hoursLamp length - 1500mmWide beam angleSuitable for general illumination in offices, supermarkets, department stores, parking lotsSuitable for operation with electromagnetic gears/CCG and direct mains operation (220-240V)2-Year warranty




PRODUCT OVERVIEW

|                                 |                                                                 |
|---------------------------------|-----------------------------------------------------------------|
| Product name                    | ToLEDo T8 V4 5FT 2300LM 840 25K                                 |
| Technology                      | LED                                                             |
| Watt (Rated) (W)                | 22                                                              |
| Lamp shape                      | Tube, double-ended                                              |
| Type                            | LED exchangeable                                                |
| Cap/Base                        | G13                                                             |
| Lamp finish                     | Opal                                                            |
| Fixture rating                  | Open                                                            |
| General application             | Education, Logistics & Industry, Office, Residential & Consumer |
| ETIM Class                      | EC001959                                                        |
| E-number FI                     | 4941323                                                         |
| Warranty                        | 2 years                                                         |
| Luminous flux (lm)              | 2300                                                            |
| Colour temperature (K)          | 4000                                                            |
| Light colour                    | Cool White                                                      |
| CRI (Ra)                        | 80                                                              |
| Colour Variation Initial (SDCM) | SDCM6                                                           |
| Beam Angle (°)                  | 180                                                             |
| Photobiological Risk Group      | RG0                                                             |
| Wattage (W)                     | 22                                                              |
| Dimmable                        | No                                                              |
| Average life (Nominal) (h)      | 25000                                                           |
| IP rating                       | IP20                                                            |
| Product EAN number              | 5410288293042                                                   |

PHOTOMETRY



ToLEDo NEOS T8 CCG and AC  
*ToLEDo T8 V4 5FT 2300LM 840 25K*  
0029304



TECHNICAL DRAWINGS

