

Sylvania Granit DALI  
Granit IP65 DALI 13000lm 840 MB  
0039617



- Product features**
- Integrated LED highbay; Black aluminium housing; 13000Lm; 93 W; 140 Lm/W; 4000K; Drive current: 1600mA; CRI 80; 55° beam angle; DALI dimmable; IP65; IK08; Lifespan L80:B50 90,000 hrs; (D x H) 308 x 179 mm; 1.5 m mains cable; 1.5 m control cable; 1.2 m chain length including hooks.

PRODUCT OVERVIEW

|                                 |                                 |
|---------------------------------|---------------------------------|
| Product name                    | Granit IP65 DALI 13000lm 840 MB |
| Technology                      | LED                             |
| Housing                         | Aluminium                       |
| Mount                           | Suspended                       |
| Fixture rating                  | Enclosed                        |
| General application             | Logistics & Industry            |
| ETIM Class                      | EC001716                        |
| E-number FI                     | 4357014                         |
| Warranty                        | 5 years                         |
| Fixture luminous flux (lm)      | 13000                           |
| Luminaire efficacy (lm/W)       | 140                             |
| Colour temperature (K)          | 4000                            |
| Light colour                    | Neutral White                   |
| CRI (Ra)                        | 80                              |
| Colour Variation Initial (SDCM) | SDCM3                           |
| Beam Angle (°)                  | 55                              |
| Glare control                   | < 22                            |
| Photobiological Risk Group      | RG1                             |
| Total power consumption (W)     | 93                              |
| Electrical protection           | Class I                         |
| Control gear type               | LED driver constant current     |
| Dimmable                        | Yes                             |
| Dimming method                  | DALI                            |
| LED Flickering Rate             | Low (6% - 20%)                  |
| Housing colour                  | Black                           |
| IP rating                       | IP65                            |
| IK rating                       | IK08                            |
| Product EAN number              | 5410288396170                   |

PHOTOMETRY

TECHNICAL DRAWINGS