

SylSafe Bay  
SylSafe Bay MB C EM3 NM MS  
0041735



Product features

- SylSafe Bay MB C EM3 NM MS is a dust and waterproof surface mounted emergency luminaire for industrial applications. Midbay optics for medium ceiling heights. Non-maintained 3hr emergency duration with NiMH rechargeable battery. Recharge period 24 hours. 200lm, 3W, IK03, IP65. Power Factor 0.44. Class II electrical construction.



PRODUCT OVERVIEW

|                                |                                                                                   |
|--------------------------------|-----------------------------------------------------------------------------------|
| Product name                   | SylSafe Bay MB C EM3 NM MS                                                        |
| Technology                     | LED                                                                               |
| Type                           | LED                                                                               |
| Mount                          | Ceiling surface mounting                                                          |
| General application            | Office, Hospitality, Retail, Museums & Galleries, Education, Logistics & Industry |
| ETIM Class                     | EC001957                                                                          |
| Warranty                       | 5 years                                                                           |
| Fixture luminous flux (lm)     | 200                                                                               |
| Luminaire efficacy (lm/W)      | 67                                                                                |
| Colour temperature (K)         | 5700                                                                              |
| CRI (Ra)                       | 75                                                                                |
| Photobiological Risk Group     | RG1                                                                               |
| Luminous flux (emergency) (lm) | 200                                                                               |
| Electrical protection          | Class II                                                                          |
| Housing colour                 | White                                                                             |
| IP rating                      | IP65                                                                              |
| IK rating                      | IK03                                                                              |
| Product EAN number             | 5410288417356                                                                     |

PHOTOMETRY

TECHNICAL DRAWINGS