

START Surface IP44 DualTone
START Surface IP44 1025lm 830/840 DualTone
0043426



Product features

- Ceiling / wall luminaire with integrated LED. Perfect solution for hallways, circulation spaces or foyer. Even and uniform light distribution with a halo lighting effect on the wall surface. Body Size diameter 250mm. Besa mounting box compatible, hole distance 51mm. DualTone functionality enables switch between 3000K and 4000K colour temperatures. Power 12W, output 1025 lumens (4000K). Non-dimmable. IK03, IP44. Low maintenance with lifespan 90,000 hours L70:B50.





PRODUCT OVERVIEW

Product name	START Surface IP44 1025lm 830/840 DualTone
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
General application	Hospitality
ETIM Class	EC002892
E-number FI	4170569
Warranty	3 years
Fixture luminous flux (lm)	1025
Luminaire efficacy (lm/W)	85
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	120
Photobiological Risk Group	RG0
Total power consumption (W)	12
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	High (>40%)
Housing colour	White
IP rating	IP44
IK rating	IK03
Product EAN number	5410288434261

PHOTOMETRY

START Surface IP44 DualTone
START Surface IP44 1025lm 830/840 DualTone
 0043426

[illegible]

	Distance [m]		Cone diameter [m]		
	50 - C180 (Half beam angle 121.9°)	C80 - C270 (Half beam angle 119.2°)	50 - C180 (Half beam angle 121.9°)	C80 - C270 (Half beam angle 119.2°)	
0.5	1.70 1.77		8/0° 8/C80 59.9° 8/C20 60.9°	200 6 35	
1.0	3.41 3.53		8/0° 8/C80 59.9° 8/C20 60.9°	247 15 15	
1.5	5.11 5.30		8/0° 8/C80 59.9° 8/C20 60.9°	110 1 3	
2.0	6.82 7.07		8/0° 8/C80 59.9° 8/C20 60.9°	62 4 4	
2.5	8.52 8.84		8/0° 8/C80 59.9° 8/C20 60.9°	40 2 2	
3.0	10.23 10.60		8/0° 8/C80 59.9° 8/C20 60.9°	27 2 2	

TECHNICAL DRAWINGS

