

Start Surface Slim IP54 - Round  
START SURFACE SLIM IP54 ROUND 1500LM 2CCT D WH  
0043510



- Product features**
- Ceiling / wall round luminaire with integrated LED. Perfect solution for corridors, circulation areas or bathrooms. Even and uniform light in a slim but robust design. Power 15W, lumen output 1500 lumens, lumen efficacy 100 lm/W, dual color temperature (3000K/4000K). Supplied with phase dimming driver (leading edge/trailing edge). Mains Voltage 220-240V~. Body Size: 220mm diameter x 53mm height. IK07, IP54 Protection rating. PC Polycarbonate Opal diffuser.Low maintenance with 58000 hours LED lifespan expectancy. Warranty: 3 years.

PRODUCT OVERVIEW

|                                 |                                                |
|---------------------------------|------------------------------------------------|
| Product name                    | START SURFACE SLIM IP54 ROUND 1500LM 2CCT D WH |
| Technology                      | LED                                            |
| Cap/Base                        | N/A                                            |
| Housing                         | PC Polycarbonate                               |
| Mount                           | Ceiling surface mounting, Wall surface mounted |
| General application             | Hospitality                                    |
| ETIM Class                      | EC002892                                       |
| E-number FI                     | 4278347                                        |
| Warranty                        | 3 years                                        |
| Fixture luminous flux (lm)      | 1500                                           |
| Luminaire efficacy (lm/W)       | 100                                            |
| Light colour                    | Warm White or Neutral White                    |
| CRI (Ra)                        | 80                                             |
| Colour Variation Initial (SDCM) | SDCM4                                          |
| Beam Angle (°)                  | 120                                            |
| Photobiological Risk Group      | RG0                                            |
| Total power consumption (W)     | 15                                             |
| Electrical protection           | Class II                                       |
| Control gear type               | LED driver constant current                    |
| Dimmable                        | Yes                                            |
| Dimming method                  | Mains: leading / trailing edge                 |
| LED Flickering Rate             | Ultra low (5% or less)                         |
| Housing colour                  | White                                          |
| IP rating                       | IP54                                           |
| IK rating                       | IK07                                           |
| Product EAN number              | 5410288435107                                  |

PHOTOMETRY

TECHNICAL DRAWINGS