

Start Surface IP66 Ø350mm Emergency  
START SURFACE IP66 1450LM 830 EM3 IK10 BLK  
0049010



Product features

- LED exterior surface mounted luminaire, 350mm diameter, 1450lm as max. lumen output, 14W max. power consumption, 104lm/W efficacy, 3000K color temperature, CRI80, IP66, IK10, 50,000 hours (L70), black housing, vandal resistant. Integrated emergency, 3 hours, supplied with anti-theft screws



PRODUCT OVERVIEW

|                                 |                                            |
|---------------------------------|--------------------------------------------|
| Product name                    | START SURFACE IP66 1450LM 830 EM3 IK10 BLK |
| Technology                      | LED                                        |
| Cap/Base                        | N/A                                        |
| Housing                         | PC Polycarbonate                           |
| Mount                           | Ceiling surface mounting                   |
| Environment                     | Indoor, Outdoor                            |
| General application             | Hospitality                                |
| ETIM Class                      | EC002892                                   |
| Warranty                        | 5 years                                    |
| Fixture luminous flux (lm)      | 1450                                       |
| Luminaire efficacy (lm/W)       | 85                                         |
| LOR (%)                         | 100                                        |
| Colour temperature (K)          | 3000                                       |
| Colour Code                     | 830                                        |
| Light colour                    | Warm White                                 |
| CRI (Ra)                        | 80                                         |
| Colour Variation Initial (SDCM) | SDCM6                                      |
| Beam Angle (°)                  | 120                                        |
| Glare control                   | < 25                                       |
| Photobiological Risk Group      | RG0                                        |
| Luminous flux (emergency) (lm)  | 124                                        |
| Total power consumption (W)     | 17                                         |
| Electrical protection           | Class II                                   |
| Control gear type               | LED driver constant current                |
| Control gear mounting           | Integrated                                 |
| Dimmable                        | No                                         |
| Dimming method                  | N/A                                        |
| LED Flickering Rate             | Ultra low (5% or less)                     |
| Housing colour                  | RAL 9011 - Graphite black                  |
| IP rating                       | IP66                                       |
| IK rating                       | IK10                                       |
| Product EAN number              | 5410288490106                              |



Start Surface IP66 Ø350mm Emergency  
*START SURFACE IP66 1450LM 830 EM3 IK10 BLK*  
0049010

---

PHOTOMETRY

---

TECHNICAL DRAWINGS

---