

Interrata Fixed
INTERRATA XS IP67 FROSTED 100LM 830
0049036



- Product features**
- Round shaped in-ground luminaire with fixed light module, walk-over for pressure loads to 500kg (5kN), comes with 2m 3x1mm2 flying lead and recessing tube, aluminium housing with Stainless steel (SS316) decorative ring and frosted glass diffuser, IP67, IK10, Class I, non-dimmable, 115lm, 3.5W, 33lm/W, CRI80, 100° beam angle, 50000 hrs L70 B50 lumen maintenance, 100mm diameter, 129mm recessing tube height, 0.42kg weight.

PRODUCT OVERVIEW

Product name	INTERRATA XS IP67 FROSTED 100LM 830
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ground recessed
General application	Hospitality, Museums & Galleries, Office, Residential & Consumer
ETIM Class	EC000758
E-number FI	4579499
Warranty	5 years
Fixture luminous flux (lm)	115
Luminaire efficacy (lm/W)	33
Colour temperature (K)	3000
Colour Code	830
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	100
Photobiological Risk Group	RG0
Total power consumption (W)	3.5
Electrical protection	Class I
Dimmable	No
LED Flickering Rate	Low (6% - 20%)
Housing colour	Stainless steel
IP rating	IP67
IK rating	IK10
Product EAN number	5410288490366

PHOTOMETRY

TECHNICAL DRAWINGS