

Start Surface IP66 Ø350mm DALI  
START SURFACE IP66 1450LM 830 IK10 DALI EM3 WHT  
0049249



- Product features**
- LED exterior surface mounted luminaire, 350mm diameter, 1450lm as max. lumen output, 15W max. power consumption, 97lm/W efficacy, 3000K color temperature, CRI80, IP66, IK10, 60,000 hours (L70), white housing, vandal resistant. DALI and DALI 2 dimming compatibility. Integrated emergency, 3 hours, supplied with anti-theft screws



PRODUCT OVERVIEW

|                                 |                                                 |
|---------------------------------|-------------------------------------------------|
| Product name                    | START SURFACE IP66 1450LM 830 IK10 DALI EM3 WHT |
| Technology                      | LED                                             |
| Cap/Base                        | N/A                                             |
| Housing                         | PC Polycarbonate                                |
| Mount                           | Ceiling surface mounting                        |
| Environment                     | Indoor, Outdoor                                 |
| General application             | Hospitality                                     |
| ETIM Class                      | EC002892                                        |
| Warranty                        | 5 years                                         |
| Fixture luminous flux (lm)      | 1450                                            |
| Luminaire efficacy (lm/W)       | 86                                              |
| LOR (%)                         | 100                                             |
| Colour temperature (K)          | 3000                                            |
| Colour Code                     | 830                                             |
| Light colour                    | Warm White                                      |
| CRI (Ra)                        | 80                                              |
| Colour Variation Initial (SDCM) | SDCM6                                           |
| Beam Angle (°)                  | 120                                             |
| Glare control                   | < 25                                            |
| Photobiological Risk Group      | RG0                                             |
| Total power consumption (W)     | 17                                              |
| Electrical protection           | Class II                                        |
| Control gear type               | LED driver constant current                     |
| Control gear mounting           | Integrated                                      |
| Dimmable                        | Yes                                             |
| Dimming method                  | DALI                                            |
| Minimum dimming level (%)       | 1                                               |
| LED Flickering Rate             | Ultra low (5% or less)                          |
| Housing colour                  | RAL 9003 - Signal white                         |
| IP rating                       | IP66                                            |
| IK rating                       | IK10                                            |
| Product EAN number              | 5410288492490                                   |



Start Surface IP66 Ø350mm DALI

*START SURFACE IP66 1450LM 830 IK10 DALI EM3 WHT*

0049249

---

PHOTOMETRY

---

TECHNICAL DRAWINGS