

Start Flood Flat without PIR  
Start Flood Flat IP65 7000LM 840 Black  
0050122



Product features

- The streamlined, durable, lightweight die-cast aluminium body makes Start Flood Flat a perfect choice for building facades, car parks, garages and construction areas. The product includes 1 m pre-wired stripped cable and fitting bracket for quick and easy installation and the universal mounting bracket allows wall or surface mounting with the possibility of vertical tilting. Black (RAL9017) housing, white reflector, 7000 lm, 63 W, 111 lm/W, 4000K, non dimmable, CRI>80, IP65, IK07, Class I, lifespan L70:B50: 90000 hrs, 195 x 250 x 33 mm (L x W x H). Weight: 1.19kg.




PRODUCT OVERVIEW

|                                 |                                        |
|---------------------------------|----------------------------------------|
| Product name                    | Start Flood Flat IP65 7000LM 840 Black |
| Technology                      | LED                                    |
| Cap/Base                        | N/A                                    |
| General application             | Residential & Consumer                 |
| ETIM Class                      | EC001744                               |
| E-number FI                     | 4579535                                |
| Warranty                        | 3 years                                |
| Fixture luminous flux (lm)      | 7000                                   |
| Luminaire efficacy (lm/W)       | 111                                    |
| Colour temperature (K)          | 4000                                   |
| Light colour                    | Neutral White                          |
| CRI (Ra)                        | 80                                     |
| Colour Variation Initial (SDCM) | SDCM5                                  |
| Beam Angle (°)                  | 110                                    |
| Photobiological Risk Group      | RG1                                    |
| Total power consumption (W)     | 63                                     |
| Electrical protection           | Class I                                |
| Dimmable                        | No                                     |
| Dimming method                  | N/A                                    |
| LED Flickering Rate             | Low (6% - 20%)                         |
| Housing colour                  | Black                                  |
| IP rating                       | IP65                                   |
| IK rating                       | IK07                                   |
| Product EAN number              | 5410288501222                          |

PHOTOMETRY

Start Flood Flat without PIR  
Start Flood Flat IP65 7000LM 840 Black  
0050122



TECHNICAL DRAWINGS

