


Start Waterproof LED G3 fixed output
START Waterproof Single 1500 IP65 4000lm 840 QC
0067973



Product features

- Start Waterproof, integrated LED weatherproof luminaire, with UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing, Polycarbonate diffuser, 3950 lm, 35 W, 120 lm/W, 4000 K, drive current 350 mA, Non dimmable with quick connector, CRI80, IP65, IK08, Class I, nominal average life (h):50000, 1578 mm x 84 mm x 75 mm ,energy class: A++ A+ A, D-mark




PRODUCT OVERVIEW

Product name	START Waterproof Single 1500 IP65 4000lm 840 QC
Technology	LED
Housing	PC Polycarbonate
Fixture rating	Enclosed
General application	Logistics & Industry
ETIM Class	EC002892
Warranty	5 years
Fixture luminous flux (lm)	3950
Luminaire efficacy (lm/W)	113
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Glare control	< 25
Photobiological Risk Group	RG0
Total power consumption (W)	35
Electrical protection	Class I
Dimmable	No
Dimming method	N/A
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288679730

PHOTOMETRY

Start Waterproof LED G3 fixed output
START Waterproof Single 1500 IP65 4000lm 840 QC
0067973



TECHNICAL DRAWINGS

