

Giotto LED 335
GIOTTO 335 4000K RECESSED DALI EMERGENCY
3034822



Product features

- Ambient and decorative round, recessed mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 2350lm, 19.5W, 121lm/W, 4000K, CRI 80, DALI, integral 3 hour maintained emergency, 120,000 hours lumen maintenance (L70:B50). Drive current: 600mA, IP44, IK10, Class I, 220-240V.




PRODUCT OVERVIEW

Product name	GIOTTO 335 4000K RECESSED DALI EMERGENCY
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
Environment	Indoor
General application	Hospitality, Logistics & Industry
ETIM Class	EC002892
Warranty	5 years
Fixture luminous flux (lm)	2350
Luminous flux (lm)	2350
Luminaire efficacy (lm/W)	121
Colour temperature (K)	4000
Colour Code	840
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Glare control	< 26
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	155
Luminous flux (emergency) (lm)	155
Total power consumption (W)	19.5
Electrical protection	Class I
Control gear type	LED driver constant current
Control gear mounting	Integrated
Dimmable	Yes
Dimming method	DALI
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	White
IP rating	IP44
IK rating	IK10

Giotto LED 335
GIOTTO 335 4000K RECESSED DALI EMERGENCY
3034822

Product EAN number 8711971348221

PHOTOMETRY



TECHNICAL DRAWINGS

