

# PRODUCT DATASHEET SMART+ Wifi Decor Wood Ceiling TW

Smart+ Wood | Smart+ Decor design luminaires with WiFi technology



## Areas of application

- Entrance areas
- Living rooms
- Bedrooms
- Offices

# **Product benefits**

- Elegant design

### **Product features**

- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Decorative Luminaire
- Housing material: metal and wood



# **TECHNICAL DATA**

# Electrical data

Nominal wattage	8.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	43.000 mA
Power factor $\lambda$	≥0.5
Total harmonic distortion	< 20 %
Protection class	Ш


## Photometrical data

Luminous flux	300 lm	
Total luminous flux of contained light sources	640 lm	
Luminous efficacy	37 lm/W	
Color temperature	30006500 K	
Reference control setting of contained light source (Kelvin)	3000 К <sup>1)</sup>	
Light color (designation)	Tunable White	
Color rendering index Ra	> 80	
Standard deviation of color matching	< 6 sdcm	
Flickering metric (Pst LM)	-	
Stroboscope effect metric (SVM)	-	
Photobiological safety group acc. to EN62778	RG0	
Photobiological safety group acc. to EN62471	RG0	

 $<sup>1) \ {\</sup>hbox{Performing a reset will restore the default values set by the manufacturer}} \\$ 

# **Dimensions & Weight**

Length	100.00 mm
Width	100.00 mm
Height	130.00 mm
Product weight	450.00 g



# Materials & Colors

Product color	Wood decor
Housing color	Wood decor
Body material	Wood
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-20+40 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Application environment	Indoor
LED module replaceable	Not replaceable
With light source	Yes

# Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

# Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No

Ball shot safe	No
----------------	----

## Additional product data

Product remark	Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.
----------------	--

# **EQUIPMENT / ACCESSORIES**

- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)
- Complete mounting and connecting accessories included

### **DOWNLOAD DATA**

	Documents and certificates
POF	User instruction
POF	Installation guide
POF	Declarations Of Conformity CE
POF	Declarations Of Conformity UKCA

# **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075757660	Folding box 1	122 mm x 122 mm x 153 mm	505.00 g	2.28 dm <sup>3</sup>
4058075757677	Shipping box 4	265 mm x 265 mm x 178 mm	2430.00 g	12.50 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.