

PRODUCT DATASHEET

Endura Hybrid Olona 50cm 2W Dark Gray

Endura Hybrid Bollard | Hybrid bollard luminaires capable of using both, solar energy and power from electric grid



Areas of application

- Gardens and other outdoor areas
- Patios, balconies

Product benefits

- Capable of using both, solar energy and power from electric grid
- Easy installation and tool-free electrical connection without professional knowledge, independent from power supply
- 12V direct current voltage for highest safety for human and animal
- Product types for different usecases available
- Sustainable energy

Product features

- Maximum connected load per solar panel = 24W
- IP67 protection of connection plugs
- When connected to the power grid, luminaire automatically switches to mains current once solar panel battery runs out of energy
- IP44 protection of luminaires
- Stainless steel housing

TECHNICAL DATA

Electrical data

Nominal wattage	2.00 W
Nominal voltage	12 V
Nominal current	167.000 mA
Protection class	III
Operating mode	Mains voltage

Photometrical data

Luminous flux	140 lm
Total luminous flux of contained light sources	250 lm
Luminous efficacy	70 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥ 80
Standard deviation of color matching	≤6 sdc _m
Flickering metric (Pst LM)	<1 %
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	120 °

Dimensions & Weight

Diameter	133.00 mm
Height	500.00 mm
Product weight	550.00 g
Cable length	300 mm



Materials & Colors

Product color	Dark gray
Housing color	Dark gray
Body material	Stainless steel
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20...40 °C
Type of connection	Fast connector
Type of protection	IP44
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Application environment	Outdoor
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	25000 h ¹⁾
Number of switching cycles	12500

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No

Additional product data

Product remark	Available from January 2024
----------------	-----------------------------

DOWNLOAD DATA

Documents and certificates	
	User instruction
	Packaging insert

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075834484	Folding box 1	142 mm x 142 mm x 513 mm	732.00 g	10.34 dm ³
4058075834491	Shipping box 4	300 mm x 300 mm x 538 mm	3760.00 g	48.42 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.