

# PRODUCT DATASHEET

## DL ALU DALI DN 150 14 W 4000 K IP44/IP20 WT

DOWNLIGHT ALU DALI | Downlight luminaires with aluminum housing and DALI driver



VALUE  
CLASS

### Areas of application

- Direct replacement for luminaires with compact fluorescent lamps
- General illumination
- Public areas
- Stairways
- Corridors
- Foyers
- Shops

### Product benefits

- Advanced functionality due to already included DALI driver
- DALI driver with individual luminaire current set-up already installed
- High luminous efficacy
- Energy savings up to 60 % (compared to luminaires that use CFL lamps)
- Very homogenous light
- Functional design
- Easy installation with fast connection
- 5 years guarantee

### Product features



- Advanced applications with DALI light installations
- Diameter of required ceiling cut-out: 150 mm or 200 mm (depending on version)
- Type of protection: IP44

---

**TECHNICAL DATA****Electrical data**


|                                                             |                     |
|-------------------------------------------------------------|---------------------|
| Nominal wattage                                             | 14.00 W             |
| Nominal voltage                                             | 220...240 V         |
| Mains frequency                                             | 0/50/60 Hz          |
| Nominal current                                             | 100.000 mA          |
| Inrush current                                              | 20 A                |
| Inrush current time $T_{h50}$                               | 140 $\mu$ s         |
| Max. number of luminaires per miniature circuit breaker B16 | 32                  |
| Max. number of luminaires per miniature circuit breaker C10 | 31                  |
| Max. number of luminaires per miniature circuit breaker C16 | 53                  |
| Power factor $\lambda$                                      | > 0.90              |
| Total harmonic distortion                                   | < 20 %              |
| Protection class                                            | II                  |
| Operating mode                                              | External LED driver |

**Photometrical data**

|                                              |                      |
|----------------------------------------------|----------------------|
| Luminous flux                                | 1260 lm              |
| Luminous efficacy                            | 90 lm/W              |
| Color temperature                            | 4000 K               |
| Light color (designation)                    | Cool White           |
| Color rendering index Ra                     | > 80                 |
| Standard deviation of color matching         | < 6 sdc <sub>m</sub> |
| Luminous intensity                           | -                    |
| Flickering metric (Pst LM)                   | -                    |
| Stroboscope effect metric (SVM)              | -                    |
| Photobiological safety group acc. to EN62778 | RG0                  |
| Photobiological safety group acc. to EN62471 | RG0                  |
| Beam angle                                   | 100 °                |




LDC typ cone



LDC typ polar

Dimensions & Weight

|                |           |
|----------------|-----------|
| Diameter       | 160.00 mm |
| Height         | 52.00 mm  |
| Product weight | 360.00 g  |



Materials & Colors

|                                            |                               |
|--------------------------------------------|-------------------------------|
| Product color                              | White                         |
| Housing color                              | White                         |
| Body material                              | Aluminum                      |
| Cover material                             | Polymethylmethacrylate (PMMA) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C                        |
| Mercury content                            | 0.0 mg                        |

### Application & Mounting

|                                        |                            |
|----------------------------------------|----------------------------|
| Ambient temperature range              | -20...+45 °C               |
| Type of connection                     | Screwless terminal, 5-Pole |
| Type of protection                     | IP44/IP20                  |
| Protection class IK (shock resistance) | IK02                       |
| Dimmable                               | Yes                        |
| Type of dimming                        | DALI                       |
| Mounting type                          | Recessed                   |
| Mounting location                      | Ceiling                    |
| Application environment                | Indoor                     |
| Mounting diameter                      | 150 mm                     |
| Mounting depth                         | 100 mm                     |
| LED module replaceable                 | Not replaceable            |
| With light source                      | Yes                        |

### Lifespan

|                            |                       |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C  | 50000 h <sup>1)</sup> |
| Lifespan L80/B10 at 25 °C  | 45000 h <sup>1)</sup> |
| Lifespan L90/B10 at 25 °C  | 30000 h               |
| Number of switching cycles | 100000                |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Certificates & Standards

|                                                      |               |
|------------------------------------------------------|---------------|
| Standards                                            | CE / CB / EAC |
| Luminaire with limited surface temperature, "D sign" | No            |
| Ball shot safe                                       | No            |

### Additional product data

|                       |              |
|-----------------------|--------------|
| Number of illuminants | Not relevant |
|-----------------------|--------------|

DOWNLOAD DATA

| Documents and certificates                                                          |                                 |
|-------------------------------------------------------------------------------------|---------------------------------|
|    | User instruction                |
|    | Addon Technical Information     |
|    | Declarations Of Conformity CE   |
|    | Declarations Of Conformity UKCA |
| Photometric and lighting design files                                               |                                 |
|    | IES file (IES)                  |
|    | LDT file (Eulumdat)             |
|    | ULD file (DIALux)               |
|  | ROLF file (RELUX)               |
|  | UGR file (UGR table)            |
|  | LDC typ cone                    |
|  | LDC typ polar                   |
| CAD/BIM files                                                                       |                                 |
|  | BIM_Revit_3D                    |
|  | CAD_STEP_3D                     |
| Tender texts                                                                        |                                 |
|  | Tender documents                |


LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume   |
|---------------|------------------------------|--------------------------------------|--------------|----------|
| 4058075202634 | Folding box<br>1             | 322 mm x 222 mm x 114 mm             | 525.00 g     | 8.15 dm³ |

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075202641 | Shipping box<br>8            | 658 mm x 466 mm x 263 mm             | 4955.00 g    | 80.64 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



References / Links

– For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.