

# PRODUCT DATASHEET LED SPOT G9 2x2 W 2700

LED SPOT | Ceiling mounted luminaires available as GU10 or G9 spot luminaires



### Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Kitchens, workspaces
- Ceiling and wall surface mounting

## **Product benefits**

- Energy savings of up to 90 % compared to halogen lamp spotlights
- Timeless design
- Flexible thanks to replaceable LED lamps
- Easy mounting

### **Product features**

- Luminaire family features five versions with up to 6 spot heads
- Available as GU10 or G9 spot luminaires
- Housing surface made of brushed nickel
- G9 spot versions with diffuser made of frosted glass
- Adjustable head



### **TECHNICAL DATA**

### Electrical data


Nominal wattage	3.80 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Power factor $\lambda$	> 0.5
Protection class	T. Control of the con
Operating mode	Mains voltage

# Photometrical data

Luminous flux	400 lm
Luminous efficacy	105 lm/W
Color temperature	2700 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Beam angle	120 °

# **Dimensions & Weight**

Length	275.00 mm
Width	80.00 mm
Height	160.00 mm
Product weight	431.00 g



### Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Aluminum
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-20+40 °C
Type of connection	Screw terminal
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Indoor
Adjustable	Yes
With light source	Yes
Holder designation	G9

# Lifespan

Lifespan L70/B50 at 25 °C	25000 h <sup>1)</sup>
Number of switching cycles	15000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Certificates & Standards

Standards	CE / EAC / REACH / RoHS
Additional product data	
Number of illuminants	2

# **EQUIPMENT / ACCESSORIES**

- Equipped with PAR16 or PIN G9 LED lamps
- Complete mounting and connecting accessories included

### **DOWNLOAD DATA**

	Documents and certificates
POF	User instruction
PDF	Packaging insert
PDF	Declarations Of Conformity CE

### **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075268029	Folding box 1	97 mm x 127 mm x 293 mm	606.00 g	3.61 dm <sup>3</sup>
4058075268036	Shipping box 8	400 mm x 265 mm x 315 mm	5334.00 g	33.39 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.