

# PRODUCT DATASHEET

## LUNETTA LED White

LUNETTA® USB | Socket night light with USB outlet and phone-parking possibility



### Areas of application

- Bedrooms
- Children's bedrooms
- For indoor use only

### Product benefits

- Automatically switches on and off according to the amount of available daylight
- Plug and Play due to EU Plug
- Energy-efficient thanks to LED technology

### Product features

- Micro USB port with charging function
- Integrated phone parking possibility in the back
- Integrated day/night sensor



TECHNICAL DATA

Electrical data


|                                                             |               |
|-------------------------------------------------------------|---------------|
| Nominal wattage                                             | 13.00 W       |
| Nominal voltage                                             | 220...240 V   |
| Mains frequency                                             | 50...60 Hz    |
| Nominal current                                             | 160.000 mA    |
| Max. number of luminaires per miniature circuit breaker C10 | -             |
| Protection class                                            | II            |
| Operating mode                                              | Mains voltage |

Photometrical data

|                           |            |
|---------------------------|------------|
| Luminous flux             | 3 lm       |
| Color temperature         | 3000 K     |
| Light color (designation) | Warm White |
| Color rendering index Ra  | ≥80        |

Dimensions & Weight

|                |          |
|----------------|----------|
| Diameter       | 90.00 mm |
| Height         | 80.00 mm |
| Product weight | 86.00 g  |



Materials & Colors

|                                 |                                                          |
|---------------------------------|----------------------------------------------------------|
| Product color                   | White                                                    |
| Housing color                   | White                                                    |
| Body material                   | Polycarbonate (PC) Acrylonitrile butadiene styrene (ABS) |
| Light emitting surface material | Plastic                                                  |
| Mercury content                 | 0.0 mg                                                   |

## Application & Mounting

|                           |                  |
|---------------------------|------------------|
| Ambient temperature range | -20...+40 °C     |
| Type of connection        | Plug type C (EU) |
| Type of protection        | IP20             |
| Dimmable                  | No               |
| Mounting type             | Surface          |
| Mounting location         | Socket           |
| Application environment   | Indoor           |
| LED module replaceable    | Not replaceable  |
| With light source         | Yes              |

## Lifespan

|                           |                       |
|---------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C | 25000 h <sup>1)</sup> |
|---------------------------|-----------------------|

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Control gear

|                        |       |
|------------------------|-------|
| Nominal output current | 2.1 A |
|------------------------|-------|

## Certificates & Standards

|           |          |
|-----------|----------|
| Standards | CE / EAC |
|-----------|----------|

## DOWNLOAD DATA

| Documents and certificates                                                         |                               |
|------------------------------------------------------------------------------------|-------------------------------|
|  | Packaging insert              |
|  | Declarations Of Conformity CE |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075266902 | Blister<br>1                 | 82 mm x 140 mm x 195 mm              | 107.00 g     | 2.24 dm <sup>3</sup>  |
| 4058075266919 | Shipping box<br>6            | 504 mm x 154 mm x 210 mm             | 850.00 g     | 16.30 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.