

PRODUCT DATASHEET ENDURA Style Pyramid 50cm Post 9W

ENDURA STYLE PYRAMID | Stainless steel wall luminaires and bollards with indirect illumination



Areas of application

- Building facades
- Entrance lighting
- Patios, balconies

Product benefits

- Easy and quick installation
- Energy-efficient thanks to LED technology

Product features

- Bright and functional outdoor LED luminaires
- Stainless steel housing
- Type of protection: IP44



TECHNICAL DATA

Electrical data


| Nominal wattage | 9.00 W |
|------------------------|---------------|
| Nominal voltage | 220240 V |
| Mains frequency | 5060 Hz |
| Power factor λ | > 0.5 |
| Protection class | 1 |
| Operating mode | Mains voltage |

Photometrical data

| Luminous flux | 600 lm | |
|------------------------------------------------|------------|--|
| Total luminous flux of contained light sources | 1000 lm | |
| Luminous efficacy | 67 lm/W | |
| Color temperature | 3000 K | |
| Light color (designation) | Warm White | |
| Color rendering index Ra | ≥80 | |
| Standard deviation of color matching | < 6 sdcm | |
| Beam angle | 90 ° | |

Dimensions & Weight

| Length | 100.00 mm |
|----------------|-----------|
| Width | 100.00 mm |
| Height | 500.00 mm |
| Product weight | 1800.00 g |



Materials & Colors

| Product color | Steel |
|----------------|--------------------|
| Housing color | Steel |
| Body material | Stainless steel |
| Cover material | Polycarbonate (PC) |

Application & Mounting

| Ambient temperature range | -20+40 °C | |
|---------------------------|-----------------------------|--|
| Type of connection | Terminal, 3-Pole (L, N, PE) | |
| Type of protection | IP44 | |
| Dimmable | No | |
| Mounting type | Surface | |
| Mounting location | Ground | |
| Application environment | Outdoor | |
| LED module replaceable | Not replaceable | |
| With light source | Yes | |

Lifespan

| Lifespan L70/B50 at 25 °C | 25000 h ¹⁾ |
|----------------------------|-----------------------|
| Number of switching cycles | 12500 |

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

| Standards | CE / EAC / UKCA |
|------------------------------------------------------|-----------------|
| Luminaire with limited surface temperature, "D sign" | No |

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

DOWNLOAD DATA

| | Documents and certificates |
|-----|----------------------------|
| PDF | User instruction |
| PDF | Packaging insert |

| | Documents and certificates |
|-----|---------------------------------|
| PDF | Declarations Of Conformity CE |
| PDF | Declarations Of Conformity UKCA |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075477919 | Folding box 1 | 120 mm x 120 mm x 520 mm | 1928.00 g | 7.49 dm ³ |
| 4058075477926 | Shipping box 2 | 540 mm x 260 mm x 140 mm | 4308.00 g | 19.66 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.