

# PRODUCT DATASHEET

## LS P -2000/940/5

LED STRIP P 2000 | High performance LED strips with 2000 lm/m for high requirements



### Areas of application

- General indoor illumination
- Industry
- Offices, retail outlets and conference rooms
- Architecture lighting
- Decorative lighting

### Product benefits

- Great scope of design options due to long and flexible LED strips
- Easy installation, no tools required for connection
- Easy mounting on many smooth surfaces thanks to self-adhesive tape
- Maximum flexibility due to large range of accessories
- Simple connection thanks to integrated cables on both sides

### Product features

- Flexible and cuttable LED strip
- Smallest cuttable unit: 55.56 mm
- Lifetime (L70/B50): up to 50,000 h at Tc max.: 80°C
- Luminous flux: 2000 lm/m
- Very good color rendering index  $R_a$ : > 90
- Initial color consistency: < 3 SDCM
- Large range of color temperatures: from warm white to cool daylight
- Dimmable with suitable drivers, see also [www.ledvance.com/dim](http://www.ledvance.com/dim)

TECHNICAL DATA

Electrical data

|                           |           |
|---------------------------|-----------|
| Nominal wattage           | 78.00 W   |
| Construction wattage      | 78.00 W   |
| Nominal wattage per meter | 15,6 W    |
| Nominal voltage           | 24 V      |
| Input voltage range       | 23...25 V |
| Type of current           | DC        |
| Nominal current           | 3250 mA   |

Photometrical data

|                                      |          |
|--------------------------------------|----------|
| Luminous efficacy                    | 127 lm/W |
| Luminous flux                        | 9125 lm  |
| Luminous flux per meter              | 1980 lm  |
| Color temperature                    | 4000 K   |
| Color rendering index Ra             | > 90     |
| Light color LED                      | Daylight |
| Light color (designation)            | Daylight |
| Standard deviation of color matching | <3 sdcn  |

Light technical data

|                                    |          |
|------------------------------------|----------|
| Beam angle                         | 120 °    |
| Rated beam angle (half peak value) | 120.00 ° |

LED MODULE INFORMATION

|                                  |     |
|----------------------------------|-----|
| Number of LEDs per meter         | 144 |
| Number of LEDs per module        | 720 |
| Number of LEDs per smallest unit | 8   |

Dimensions & Weight



|                        |            |
|------------------------|------------|
| Length                 | 5000.00 mm |
| Length – smallest unit | 55.56 mm   |
| Cable length           | 500.000    |

|                         |                     |
|-------------------------|---------------------|
| Width                   | 8.00 mm             |
| Height                  | 1.50 mm             |
| Prewired                | Yes                 |
| Conductor cross section | 0.5 mm <sup>2</sup> |
| LED pitch               | 6.94 mm             |
| Short pitch             | Yes                 |
| Product weight          | 95.00 g             |

### Temperatures & operating conditions

|                                      |              |
|--------------------------------------|--------------|
| Ambient temperature range            | -20...+55 °C |
| Maximum temperature at tc test point | 80 °C        |

### Lifespan

|                        |         |
|------------------------|---------|
| Nominal lamp life time | 50000 h |
|------------------------|---------|

### Capabilities

|                       |                   |
|-----------------------|-------------------|
| Dimmable              | Yes <sup>1)</sup> |
| Lowest bending radius | 30,0 mm           |
| Self-adhesive         | Yes               |

<sup>1)</sup> Dimmable with suitable drivers, see also [www.ledvance.com/dim](http://www.ledvance.com/dim)

### Certificates & Standards

|                                          |                 |
|------------------------------------------|-----------------|
| Approval marks – approval                | CE / TUV / ENEC |
| Protection class                         | III             |
| Type of protection                       | IP00            |
| Energy class of contained light source   | E               |
| ID of contained light source             | AC38037         |
| Salt mist resistance acc. IEC 60068-2-52 | No              |
| UV resistance acc. IEC 60068-2-5         | No              |

### LOGISTICAL DATA

|                              |              |
|------------------------------|--------------|
| Temperature range at storage | -20...+80 °C |
|------------------------------|--------------|

### DOWNLOAD DATA

| Documents and certificates                                                         |                             |
|------------------------------------------------------------------------------------|-----------------------------|
|  | User instruction            |
|  | Addon Technical Information |

## Documents and certificates



Declarations Of Conformity CE

## Photometric and lighting design files



IES file (IES)



LDT file (Eulumdat)



LDC typ polar

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075707757 | Folding box<br>1             | 242 mm x 242 mm x 26 mm              | 426.00 g     | 1.52 dm <sup>3</sup>  |
| 4058075707764 | Shipping box<br>30           | 450 mm x 420 mm x 230 mm             | 7297.00 g    | 43.47 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.