

PRODUCT DATASHEET LN MAG BATTEN T5 1168

LINEAR MAGNETIC BATTEN T5 | Luminaire insert for LED TUBE T5 AC



Areas of application

- Replacement kit for modernizing existing metallic ceiling lights (T8 and T5 Fluorescent) to energy-saving LED technology
- Offices, public buildings
- Supermarkets and department stores
- Industry
- Corridors, foyers, waiting areas



Product benefits

- Retrofitting without completely replacing existing luminaires
- If necessary, the old luminaire may remain installed on the ceiling during the conversion process
- Control gear and wiring may remain in the old luminaire if necessary
- Easy replacement of the LED TUBE T5 AC allows to participate in progress of LED technology over time
- Simple and quick upgrade solution
- Integrated fuse for additional safety
- 5 years guarantee

Product features

- Available in 4 different lengths: 568 mm, 868 mm, 1168 mm and 1468 mm
- Luminaire insert for accommodating one LED TUBE T5 AC 230V
- Suitable for LED TUBE T5 AC, HE or HO, 830/840/865
- Strong neodym magnets



TECHNICAL DATA

Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	1
Operating mode	Mains voltage

Dimensions & Weight

Length	1168.00 mm
Width	25.00 mm
Height	45.00 mm
Product weight	550.00 g
Cable length	820 mm



Materials & Colors

Product color	White
Housing color	White
Body material	Steel
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+45 °C	
Temperature range at storage	-2080 °C	
Type of connection	Screwless terminal, 3-Pole	
Type of protection	IP20	
Protection class IK (shock resistance)	IK02	
Dimmable	No	
Mounting type	Surface	

Mounting location	Ceiling
Application environment	Indoor
With light source	No
Holder designation	G5

Certificates & Standards

Standards	CE / ENEC / TÜV Rheinland / UKCA / EAC	
Luminaire with limited surface temperature, "D sign"	No	
Ball shot safe	No	

Additional product data

Number of illuminants	1
-----------------------	---

DOWNLOAD DATA


	Documents and certificates
PDF	User instruction
PDF	Packaging insert
PDF	Declarations Of Conformity CE
	Tender texts
<u></u>	Tender documents


LOGISTICAL DATA


Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854009747	Folding box 1	70 mm x 1,182 mm x 37 mm	662.00 g	3.06 dm ³
4099854009754	Shipping box 10	1,204 mm x 372 mm x 90 mm	7229.00 g	40.31 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION







References / Links

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.