

PRODUCT DATASHEET

LN INV DI 1200 P 54W 930 DAVR WT

LINEAR INDIVILED DIRECT/INDIRECT 1200 DALI | Pendant luminaire for single or light line office application with CRI90 and DALI-2 IoT technology, 1200 mm



Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Offices, education, public buildings
- Single and continuous line configuration
- Direct and indirect lighting

Product benefits

- Easy upgradeability of light source and driver (EVERLOOP design)
- Homogenous light distribution and reduced glare ($UGR \leq 19$) thanks to IndiviLED® optics
- Pendant luminaires with direct light emission (70%) and indirect light emission (30%)
- High performance with CRI90 and up to 137 lm/W
- IoT-ready luminaire with DALI-2 driver, suitable for VIVARES and other Light Management Systems
- Extended services such as energy monitoring and remote maintenance possible with DALI versions
- High color consistency with SDCM 3
- Easy installation
- Low flicker light thanks to special electronic control gear
- Suitable for battery emergency installations acc. to EN 60598-2-22
- Multiple mounting options thanks to different accessories
- 5 years guarantee

Product features




- Minimalistic LEDVANCE SCALE design in extruded aluminum housing
- Includes EVERLOOP: Convenient replacement of light source and LED driver
- Linkable into seamless light line with accessories (surface or pendant mounting)
- Pendant mounting with suspension kit (to be ordered separately)
- Glow Wire Test according to IEC 60695-2-12: 850 °C
- 5-pole terminal block, cable cross section up to 5 x 2.5 mm²
- Lifetime (L80-B10): up to 70,000 h (at 25 °C)

TECHNICAL DATA**Electrical data**


Nominal wattage	54.00 W
Nominal voltage	220...240 V
Mains frequency	0/50/60 Hz
Nominal current	255.000 mA
Inrush current	0.233 A
Inrush current time T_{h50}	40 μ s
Max. number of luminaires per miniature circuit breaker B16	16
Max. number of luminaires per miniature circuit breaker C10	14
Max. number of luminaires per miniature circuit breaker C16	22
Power factor λ	≥ 0.90
Total harmonic distortion	$\leq 20 \%$
Protection class	I
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	6500 lm
Luminous efficacy	120 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	90
Standard deviation of color matching	3 sdcn
Low flicker	Yes
Flickering metric (Pst LM)	≤ 1
Stroboscope effect metric (SVM)	≤ 0.4
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	90 ° + 130 °
UGR	< 19




LDC typ cone



LDC typ polar

Dimensions & Weight

Length	1210.00 mm
Width	125.00 mm
Height	43.00 mm
Product weight	3540.00 g



Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+50 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screwless terminal, 5-Pole (L, N, PE, DA+, DA-)
Type of protection	IP20
Protection class IK (shock resistance)	IK06
Dimmable	Yes
Type of dimming	DALI2
Mounting type	Suspended
Mounting location	Ceiling
Application environment	Indoor
Adjustable	No
LED module replaceable	Only by an expert
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	100000 h ¹⁾
Lifespan L80/B10 at 25 °C	70000 h ¹⁾
Lifespan L90/B10 at 25 °C	35000 h
Number of switching cycles	25000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	1100 mA
ECG - Output ripple current	≤ 3 %
Recommended control gear	OSRAM type OTI DALI 50/220-240/1A4 NFC L

Certificates & Standards

Standards	CE / CB / ENEC / TÜV SÜD / UKCA / EAC
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

Additional product data

Product remark	Available from December 2023
Number of illuminants	2
Added function	EVERLOOP

EQUIPMENT / ACCESSORIES

- Suspension kit available for pendant luminaire version (to be ordered separately)
- Inline, corner and infill connectors available as separate accessory
- Through-wiring cable kit available

DOWNLOAD DATA

Documents and certificates	
	User instruction
	Addon Technical Information
	Packaging insert
	Declarations Of Conformity CE
	Declarations Of Conformity UKCA
Photometric and lighting design files	
	IES file (IES)
	LDT file (Eulumdat)
	UGR file (UGR table)
	LDC typ cone
	LDC typ polar




LOGISTICAL DATA




Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854135552	Folding box 1	1,253 mm x 168 mm x 88 mm	4140.00 g	18.52 dm³
4099854135569	Shipping box 2	1,277 mm x 187 mm x 189 mm	9680.00 g	45.13 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



		DRIVER		LN RV IN 0-150V AC 50/60Hz DRIVER WIT: Power 50W LN RV IN 0-150V AC 50/60Hz DRIVER WIT:			
LINEAR InduLED® DRIVING DALI		DRIVER		DIRECT	INDIRECT	Total	AC
LN RV IN 0-150V AC 50/60Hz DRIVER WIT		OPT DALI 50W 100-150V AC 15A IMPL L		100-150V AC 15A IMPL L 100-150V AC 15A IMPL L	100-150V AC 15A IMPL L 100-150V AC 15A IMPL L	100-150V AC 15A IMPL L 100-150V AC 15A IMPL L	100-150V AC 15A IMPL L 100-150V AC 15A IMPL L
LN RV IN 0-150V AC 50/60Hz DRIVER WIT		OPT DALI 50W 100-150V AC 15A IMPL L		100-150V AC 15A IMPL L 100-150V AC 15A IMPL L	100-150V AC 15A IMPL L 100-150V AC 15A IMPL L	100-150V AC 15A IMPL L 100-150V AC 15A IMPL L	100-150V AC 15A IMPL L 100-150V AC 15A IMPL L
LN RV IN 0-150V AC 50/60Hz DRIVER WIT		OPT DALI 75W 100-150V AC 15A IMPL L		100-150V AC 15A IMPL L 100-150V AC 15A IMPL L	100-150V AC 15A IMPL L 100-150V AC 15A IMPL L	100-150V AC 15A IMPL L 100-150V AC 15A IMPL L	100-150V AC 15A IMPL L 100-150V AC 15A IMPL L
LN RV IN 0-150V AC 50/60Hz DRIVER WIT		OPT DALI 75W 100-150V AC 15A IMPL L		100-150V AC 15A IMPL L 100-150V AC 15A IMPL L	100-150V AC 15A IMPL L 100-150V AC 15A IMPL L	100-150V AC 15A IMPL L 100-150V AC 15A IMPL L	100-150V AC 15A IMPL L 100-150V AC 15A IMPL L



References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.