

# PRODUCT DATASHEET

## TruSys® PFM W 70 W/4000 K

TruSys® PERFORMANCE WIDE | Luminaire inserts with wide light distribution



### Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Industry halls, high rack warehouse, garages, hardware stores
- Discounters, supermarkets

### Product benefits

- Homogenous light distribution
- Easy installation, no tools required for connection
- Energy saving and cost-effective
- Flexible application due to a range of different lumen packages and beam angles
- Rows of up to 57 (On-Off) / 66 (DALI) luminaires possible
- Versions with DALI ECG available

### Product features

- Beam angle wide: 90°
- Click into place solution with smart click buttons
- Luminous efficacy: up to 160 lm/W
- Fixed luminaire taps
- Lumen package 5600 lm, 8000 lm, 11200 lm
- Steel-sheet housing
- Lens material: PMMA



- Type of protection: IP20
- Common family design with LEDVANCE
- Lifetime (L80/B10): up to 60,000 h


---

**TECHNICAL DATA****Electrical data**


|                                                             |                       |
|-------------------------------------------------------------|-----------------------|
| Nominal wattage                                             | 70.00 W               |
| Nominal voltage                                             | 220...240 V           |
| Mains frequency                                             | 50...60 Hz            |
| Nominal current                                             | 380 mA                |
| Inrush current                                              | 32 A                  |
| Inrush current time $T_{h50}$                               | 400 $\mu$ s           |
| Max. number of luminaires per miniature circuit breaker B16 | 5                     |
| Max. number of luminaires per miniature circuit breaker C10 | 5                     |
| Max. number of luminaires per miniature circuit breaker C16 | 9                     |
| Power factor $\lambda$                                      | > 0.90                |
| Total harmonic distortion                                   | < 20 %                |
| Protection class                                            | I                     |
| Operating mode                                              | Integrated LED driver |

**Photometrical data**

|                                              |               |
|----------------------------------------------|---------------|
| Luminous flux                                | 11200 lm      |
| Luminous efficacy                            | 160 lm/W      |
| Color temperature                            | 4000 K        |
| Light color (designation)                    | Cool White    |
| Color rendering index Ra                     | $\geq 80$     |
| Standard deviation of color matching         | $\leq 3$ sdcn |
| Low flicker                                  | Yes           |
| Photobiological safety group acc. to EN62778 | RG1           |
| Beam angle                                   | 90 °          |
| UGR                                          | 21            |




LDC typ cone



LDC typ polar

Dimensions & Weight

|                |            |
|----------------|------------|
| Length         | 1500.00 mm |
| Width          | 66.80 mm   |
| Height         | 39.40 mm   |
| Product weight | 1660.00 g  |



Materials & Colors

|               |       |
|---------------|-------|
| Product color | White |
| Housing color | White |
| Body material | Steel |

|                                            |                               |
|--------------------------------------------|-------------------------------|
| Cover material                             | Polymethylmethacrylate (PMMA) |
| Light emitting surface material            | PMMA                          |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C                        |
| Mercury content                            | 0.0 mg                        |

### Application & Mounting

|                                        |                    |
|----------------------------------------|--------------------|
| Ambient temperature range              | -25...+40 °C       |
| Type of connection                     | Plug-In connection |
| Type of protection                     | IP20               |
| Protection class IK (shock resistance) | IK04               |
| Dimmable                               | No                 |
| Mounting type                          | Suspended/Surface  |
| Mounting location                      | Mounting rail      |
| Application environment                | Indoor             |
| LED module replaceable                 | Not replaceable    |
| With light source                      | Yes                |

### Lifespan

|                            |                       |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C  | 55000 h <sup>1)</sup> |
| Lifespan L80/B10 at 25 °C  | 50000 h <sup>1)</sup> |
| Lifespan L90/B10 at 25 °C  | 40000 h               |
| Number of switching cycles | 100000                |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Control gear

|                             |        |
|-----------------------------|--------|
| Output current              | 980 mA |
| ECG - Output ripple current | < 20 % |

### Certificates & Standards

|                |                      |
|----------------|----------------------|
| Standards      | CE / CB / ENEC / EAC |
| Ball shot safe | No                   |

### EQUIPMENT / ACCESSORIES

– Mounting rail with fixed integrated 5- and 8-pole cable

### DOWNLOAD DATA

## Documents and certificates



User instruction



Addon Technical Information



Declarations Of Conformity CE

## Photometric and lighting design files



IES file (IES)



LDT file (Eulumdat)



ULD file (DIALux)



ROLF file (RELUX)



UGR file (UGR table)



LDC typ cone



LDC typ polar

## CAD/BIM files



CAD\_STEP\_3D

## Tender texts



Tender documents

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075290891 | Folding box<br>1             | 83 mm x 1,571 mm x 88 mm             | 1835.00 g    | 11.47 dm <sup>3</sup> |
| 4058075290907 | Shipping box<br>4            | 1,589 mm x 194 mm x 198 mm           | 8133.00 g    | 61.04 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.