AARDBEVINGSBESTENDIGE STABILISATIEBEUGEL VR BUIS 2 1/2", DN65, ELEKTROLYT. VERZ.

CATALOG NUMBER

CSBSTU0250EG

CERTIFICATIONS

FEATURES

- Gebruik voor zowel overlangse als zijwaartse stabilisatiebeugeltoepassingen
- Een afbreekbare boutkop vergemakkelijkt de installatie en inspectie van seismische stabilisatiebeugels
- Works with 1" through 2" brace pipes to reduce inventory
- Sleufontwerp grijpt leiding vast voor extra sterkte
- Voldoet aan NFPA®-13-vereisten voor seismische diagonaalsteunen
- Meets CEN/TS 17551:2021 requirements for Seismic Sway Bracing

PRODUCTKENMERKEN

- Article Number: 404389
- Material: Steel; Cast Iron
- Finish: Elektrolytisch gegalvaniseerd
- Pipe Size: 2 1/2"

NB/DN: 65

A: 225,4 mm

B: 30,2 mm

Brace Pipe Size: 1 – 2"

Brace NB/DN: 25 – 50 mm

ADDITIONAL PRODUCT DETAILS

When installed with Schedule 10 and Schedule 40 Service Pipe, use 1" to 2" Schedule 40 NPS as brace member.

When installed with KS D 3507 and KS D 3562 Service Pipe, use 25A to 32A KS D 3562 as brace member.

FM Loads (EN 10255 L, EN10255 M and EN 10255 H Service Pipes)

Referentienummer	Horizontale capaciteit per installatiehoek van het verticale vlak							
	Lateraal				Longitudinaal			
	30°- 44°	45°- 59°	60°- 74°	75°- 90°	30°- 44°	45°- 59°	60°- 74°	75°- 90°
CSBSTU0100xx	3825 N	5425 N	6670 N	7430 N	4315 N	3200 N	3825 N	4270 N
CSBSTU0125xx	3825 N	5425 N	6670 N	7430 N	4315 N	3200 N	3825 N	4270 N
CSBSTU0150xx	3825 N	5425 N	6670 N	7430 N	4315 N	3200 N	3825 N	4270 N
CSBSTU0200xx	6805 N	9610 N	11790 N	13165 N	3870 N	3070 N	3690 N	4136 N
CSBSTU0250xx	6805 N	9610 N	11790 N	13165 N	3870 N	3070 N	3690 N	4136 N
CSBSTU0300xx	6805 N	9610 N	11790 N	13165 N	3870 N	3070 N	3690 N	4136 N
CSBSTU0400xx	6985 N	9875 N	12100 N	13480 N	6895 N	6185 N	7475 N	8320 N
CSBSTU0500xx	6985 N	9875 N	12100 N	13480 N	6895 N	6185 N	7475 N	8320 N
CSBSTU0600xx	8805 N	12500 N	15300 N	17080 N	6540 N	5205 N	6270 N	6985 N

FM Loads (4.8 mm wall and EN 10255 H Service Pipes)

Referentienummer	Horizontale capaciteit per installatiehoek van het verticale vlak							
	Lateraal				Longitudinaal			
	30°- 44°	45°- 59°	60°- 74°	75°- 90°	30°- 44°	45°- 59°	60°- 74°	75°- 90°
CSBSTU0800xx	9075 N	12855 N	15745 N	17570 N	5340 N	7560 N	9295 N	10365 N
CSBSTU1000xx	9075 N	12855 N	15745 N	17570 N	5340 N	7560 N	9295 N	10365 N

Draagvermogen naar UL (geregistreerd voor buizen)

Referentienummer	Lateraal	Longitudinaal
	Sch 10/Sch 40 Service Pipe	Sch 10/Sch 40 Service Pipe
CSBSTU0100	2914 N	2914 N
CSBSTU0125	2914 N	2914 N
CSBSTU0150	2914 N	2914 N
CSBSTU0200	2914 N	-

Draagvermogen naar UL				
Referentienummer	Lateraal		Longitudinaal	
	Sch 10/ Sch 40 Service Pipe	KS D 3507/ KS D 3562 Service Pipe	Sch 10/ Sch 40 Service Pipe	KS D 3507/ KS D 3562 Service Pipe
CSBSTU0250	8896 N	8896 N	5782 N	3025 N
CSBSTU0300	7117 N	n.v.t.	3114 N	n.v.t.
CSBSTU0400	8896 N	n.v.t.	5782 N	n.v.t.
CSBSTU0500	8896 N	n.v.t.	5782 N	n.v.t.
CSBSTU0600	4893 N	n.v.t.	4893 N	n.v.t.
CSBSTU0800	8896 N	8896 N	6094 N	6094 N
CSBSTU1000	8895 N	8896 N	8385 N	8385 N

DIAGRAMS





WAARSCHUWING

Producten van nVent moeten worden geïnstalleerd en gebruikt op de manier zoals is aangegeven in de nVent productinformatiebladen en trainingsmaterialen. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Door onjuist installeren, verkeerd gebruik, verkeerde toepassing of enige andere handeling in strijd met de instructies en waarschuwingen van nVent kan het product mogelijk niet correct werken, ernstig of fataal letsel en materiële schade veroorzaken en/of uw garantie ongeldig maken.

Noord-Amerika
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europa
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europa
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500

Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2023 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.