

SBS ISOLATING SILICONE SLEEVE, 6 MM DIA, 100 M

CATALOG NUMBER

SBS-6



CERTIFICATIONS



FEATURES

Resistant to high temperature

Cost effective sleeve for insulation

High flexibility

Halogeenvrij

PRODUCTKENMERKEN

Article Number: 554010

Material: Fiberglass; Silicone

Insulation Voltage: 2,5 kV

Max Working Voltage, IEC (Ui): 690

Max Working Voltage, UL (Vin): 690

Working Temperature: -60 to 220 °C

Flammability Rating: UL® 1441 VW-1

Diameter: 6 mm

Length: 100 m

ADDITIONAL PRODUCT DETAILS

Unit weight is per meter (3.28').

WAARSCHUWING

Producten van nVent moeten worden geïnstalleerd en gebruikt op de manier zoals is aangegeven in de nVent productinformatiebladen en trainingsmaterialen. U kunt de productinformatiebladen downloaden van www.nvent.com of opvragen bij uw nVent-klantenservice. Door onjuist installeren, verkeerd gebruik, verkeerde toepassing of enige andere handeling in strijd met de instructies en waarschuwingen van nVent kan het product mogelijk niet correct werken, ernstig of fataal letsel en materiële schade veroorzaken en/of uw garantie ongeldig maken.

Noord-Amerika

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europa

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europa

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER