

FLEXBUS ISOLEREND VERBAND FIB

CATALOG NUMBER

FLEXBANDAGE



CERTIFICATIONS



FEATURES

Intumescent wrap on the basis of butyl rubber with intumescent fire protection additives and glass-fabric reinforcement

To be used around Flexbus Conductors if the thickness of the penetration seal is < to 200mm

PRODUCTKENMERKEN

Article Number: 508152

Color: Red; Brown

Complies With: EN 13501-1; EN 1366-3

Length: 5000 mm

Width: 150 mm

Unit Weight: 3,6 kg

WAARSCHUWING

Producten van nVent moeten worden geïnstalleerd en gebruikt op de manier zoals is aangegeven in de nVent productinformatiebladen en trainingsmaterialen. U kunt de productinformatiebladen downloaden van www.nvent.com of opvragen bij uw nVent-klantenservice. Door onjuist installeren, verkeerd gebruik, verkeerde toepassing of enige andere handeling in strijd met de instructies en waarschuwingen van nVent kan het product mogelijk niet correct werken, ernstig of fataal letsel en

materiële schade veroorzaken en/of uw garantie ongeldig maken.

Noord-Amerika

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europa

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europa

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER