

PRODUCT DATASHEET

DP SLIM ECO 600 18W 840 IP65

DAMP PROOF SLIM ECO | Damp-proof luminaire with slim housing

Areas of application

- Industrial and storage facilities
- Car parks and underpasses
- Garages
- Workshops, assembly lines



Product benefits

- Evenly distributed light
- Energy savings of up to 50 % (compared to luminaires that use fluorescent lamps)
- Very slim housing

Product features

- High luminous efficacy: up to 120 lm/W
- Beam angle: 110°
- Type of protection: IP65

TECHNICAL DATA

Electrical data

Nominal wattage	18.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	90 mA
Total harmonic distortion	< 20 %
Protection class	II
Operating mode	AC Mains

Photometrical data

Luminous flux	1980 lm
Luminous efficacy	110 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	< 5 sdcm
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	110 °

LDC typ cone	LDC typ polar
--------------	---------------

Dimensions & Weight

Length	600.00 mm
Width	60.00 mm
Height	35.00 mm
Product weight	185.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Type of connection	Cable, 2-pole
Type of protection	IP65
Protection class IK (shock resistance)	IK06
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
Mounting length	250 mm
LED module replaceable	Not replaceable

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Lifespan L80/B10 at 25 °C	15000 h ¹⁾

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Emergency lighting

Type of emergency operation test	None
----------------------------------	------

Certificates & Standards

Luminaire with limited surface temperature, "D sign"	No
--	----

DOWNLOAD DATA

Photometric and lighting design files	
	UGR file (UGR table)

Photometric and lighting design files	
	LDC typ cone
	LDC typ polar

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075601574	Folding box 1	670 mm x 65 mm x 40 mm	202.00 g	1.74 dm³
4058075601581	Shipping box 18	690 mm x 260 mm x 233 mm	4141.00 g	41.80 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.