

PRODUCT DATASHEET SMART+ WiFi Tube T8EM 1500 24W 865

SMART+ Tubes with WiFi technology | SMART+ Tubes with WiFi technology



Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor applications only

Product benefits

- Wireless control via app
- Easy to install and use
- Contains no mercury
- Lower energy consumption than incandescent or halogen lamps

Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via Google Assistant and Amazon Alexa possible
- Network protocol: WiFi
- Lifetime: up to 50,000 h
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)




TECHNICAL DATA

Electrical data

Nominal wattage	24 W
Construction wattage	24.00 W
Nominal voltage	220240 V
Nominal current	195 mA
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Claimed equiv. conventional lamp power	58 W

Photometrical data

Light color (designation)	Tunable White
Lumen main.fact.at end of nom.life time	0.70
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	3100 lm
Luminous flux	3100 lm
Luminous efficacy	129 lm/W
Adjustable color temperature	27006500 K
Color temperature	27006500 K
Color rendering index Ra	83
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



Light technical data

Beam angle	160 °
Warm-up time (60 %)	< 0.50 s

Dimensions & Weight



Product weight	295.00 g
Diameter	27.00 mm
Length	1514.00 mm
Width	27.00 mm
Height	27.00 mm
Outer bulb [PICOS]	T8
Lifespan	
Number of switching cycles	200000
Lifespan	50000 h
Colors & materials	
Body material	Glass with shatter protection
Temperatures & operating conditions	
Ambient temperature range	-20+50 °C
Additional product data	
Base (standard designation)	G13
Capabilities	
Dimmable	Yes
Compatible smart home technology	Amazon Alexa / Google Assistant
Certificates & Standards	
Energy efficiency class	E

Type of protection

Energy consumption

Energy labelling regulation data acc EU 2019/2015		
Lighting technology used	LED	
Non-directional or directional	NDLS	
Mains or non-mains	MLS	

IP20

24.00 kWh/1000h

Light source cap-type (or other electric interface)	G13
Connected light source (CLS)	Yes
Color-tuneable light source	Yes
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	RANGE
Standby power	0.50
Networked standby power for CLS	0.50
Claim of equivalent power	Yes
Chromaticity coordinate x	0.458
Chromaticity coordinate y	0.410
R9 Colour rendering index	83
Beam angle correspondence	SPHERE_360
Survival factor	0.90
Displacement factor	0.70
LED light source replaces a fluorescent light source	Yes
EPREL ID	715351
Model number	AC35123

EQUIPMENT / ACCESSORIES

- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

DOWNLOAD DATA

	Documents and certificates
PDF	Installation guide
PDF	Declarations Of Conformity CE
	Photometric and lighting design files
	Spectral power distribution

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075626256	Folding box 1	27 mm x 27 mm x 1,610 mm	397.00 g	1.17 dm³
4058075626263	Shipping box 10	1,665 mm x 185 mm x 118 mm	5923.00 g	36.35 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.