

PRODUCT DATASHEET

LS P -1000/930/5/IP67

LED STRIP P 1000 P | High performance IP67 protected LED strips with 1000 lm/m for high requirements



Areas of application

- General indoor illumination
- General outdoor illumination
- Industry
- Offices, retail outlets and conference rooms
- Architecture lighting
- Decorative illumination

Product benefits

- Great scope of design options due to long and flexible LED strips
- Easy installation, no tools required for connection
- Easy mounting on many smooth surfaces thanks to self-adhesive tape
- Simple connection thanks to integrated cables on both sides
- Suitable for use in damp conditions thanks to high type of protection

Product features

- Flexible and cuttable LED strip
- Smallest cuttable unit: 55.56 mm
- Lifetime (L70/B50): 50,000 h (temperature at $T_c = 80\text{ °C}$)
- Luminous flux: 1000 lm/m
- Very good color rendering index $R_a: > 90$
- Initial color consistency: $< 3\text{ SDCM}$
- Large range of color temperatures: from warm white to cool daylight
- Dimmable with suitable drivers, see also www.ledvance.com/dim
- Type of protection: IP67
- UV resistance (acc. IEC 60068-2-5)
- Salt mist resistance (acc. IEC 60068-2-52)

TECHNICAL DATA

Electrical data

Nominal wattage	43.00 W
Construction wattage	43.00 W
Nominal wattage per meter	8.6 W
Nominal voltage	24 V
Input voltage range	23...25 V
Type of current	DC
Nominal current	1791 mA

Photometrical data

Luminous efficacy	112 lm/W
Luminous flux	4440 lm
Luminous flux per meter	965 lm
Color temperature	3000 K
Color rendering index Ra	> 90
Light color LED	Warm White
Light color (designation)	Warm White
Standard deviation of color matching	≤3 sdc _m

Light technical data

Beam angle	110 °
Rated beam angle (half peak value)	110.00 °

LED MODULE INFORMATION

Number of LEDs per meter	144
Number of LEDs per module	720
Number of LEDs per smallest unit	8

Dimensions & Weight



Length	5000.00 mm
Length – smallest unit	55.56 mm
Cable length	500.000

Width	10.00 mm
Height	4.70 mm
Prewired	Yes
Conductor cross section	0.5 mm ²
LED pitch	6.94 mm
Short pitch	Yes
Product weight	380.00 g

Colors & materials

Cover material	Silicone
----------------	----------

Temperatures & operating conditions

Ambient temperature range	-20...+55 °C
Maximum temperature at tc test point	80 °C

Lifespan

Nominal lamp life time	50000 h
------------------------	---------

Capabilities

Dimmable	Yes ¹⁾
Lowest bending radius	30,0 mm
Self-adhesive	Yes

¹⁾ Dimmable with suitable drivers, see also www.ledvance.com/dim

Certificates & Standards

Approval marks – approval	CE / TUV / ENEC
Protection class	III
Type of protection	IP67
Energy class of contained light source	F
ID of contained light source	AC38060
Salt mist resistance acc. IEC 60068-2-52	Yes
UV resistance acc. IEC 60068-2-5	Yes

LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

EQUIPMENT / ACCESSORIES

- Connectors, profiles and covers for several mounting options available
- Endcaps have to be ordered separately

DOWNLOAD DATA

Documents and certificates	
	User instruction
	Addon Technical Information
	Declarations Of Conformity CE
Photometric and lighting design files	
	IES file (IES)
	LDT file (Eulumdat)
	LDC typ polar

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075705937	Folding box 1	242 mm x 242 mm x 26 mm	426.00 g	1.52 dm³
4058075705944	Shipping box 20	550 mm x 325 mm x 270 mm	10453.00 g	48.26 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.