

# PRODUCT DATASHEET

## SMART+ Wifi Planon 1200x300mm RGB + TW

SMART+ Planon Frameless TW and Multicolor | Frameless panel luminaires with WiFi technology

---

### Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices



---

### Product benefits

- Easy and quick installation

---

### Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- RGB color control, approx. 16 million color options adjustable
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Dimmable
- Network protocol: WiFi



## TECHNICAL DATA

### Electrical data

|                                                             |               |
|-------------------------------------------------------------|---------------|
| Nominal wattage                                             | 40.00 W       |
| Nominal voltage                                             | 220...240 V   |
| Mains frequency                                             | 50...60 Hz    |
| Nominal current                                             | 203.500 mA    |
| Max. number of luminaires per miniature circuit breaker B16 | 16            |
| Max. number of luminaires per miniature circuit breaker C16 | 24            |
| Power factor $\lambda$                                      | > 0.90        |
| Total harmonic distortion                                   | < 20 %        |
| Protection class                                            | II            |
| Operating mode                                              | Mains voltage |

### Photometrical data

|                                                |                     |
|------------------------------------------------|---------------------|
| Luminous flux                                  | 3300 lm             |
| Total luminous flux of contained light sources | 4400 lm             |
| Luminous efficacy                              | 83 lm/W             |
| Color temperature                              | 3000...6500 K       |
| Light color (designation)                      | Tunable White / RGB |
| Color rendering index Ra                       | > 80                |
| Standard deviation of color matching           | < 6 sdcm            |
| Flickering metric (Pst LM)                     | $\leq 1$            |
| Stroboscope effect metric (SVM)                | $\leq 0.4$          |
| Photobiological safety group acc. to EN62778   | RG0                 |
| Photobiological safety group acc. to EN62471   | RG0                 |
| Beam angle                                     | 110 °               |

### Dimensions & Weight

|                |            |
|----------------|------------|
| Length         | 1200.00 mm |
| Width          | 300.00 mm  |
| Height         | 62.00 mm   |
| Product weight | 5020.00 g  |

## Materials & Colors

|                                            |                               |
|--------------------------------------------|-------------------------------|
| Product color                              | White                         |
| Housing color                              | White                         |
| Body material                              | Aluminum                      |
| Cover material                             | Polymethylmethacrylate (PMMA) |
| Light emitting surface material            | PMMA                          |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C                        |
| Mercury content                            | 0.0 mg                        |

## Application & Mounting

|                           |                         |
|---------------------------|-------------------------|
| Ambient temperature range | -20...+40 °C            |
| Type of connection        | Terminal, 2-Pole (L, N) |
| Type of protection        | IP20                    |
| Dimmable                  | Yes                     |
| Type of dimming           | WiFi                    |
| Mounting type             | Surface                 |
| Mounting location         | Ceiling                 |
| Application environment   | Indoor                  |
| LED module replaceable    | Not replaceable         |
| With light source         | No                      |

## Lifespan

|                            |         |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C  | 25000 h |
| Number of switching cycles | 15000   |

## Certificates & Standards

|                                                      |                 |
|------------------------------------------------------|-----------------|
| Standards                                            | CE / EAC / UKCA |
| Luminaire with limited surface temperature, "D sign" | No              |

## Additional product data

|                |                                                                                                                                  |
|----------------|----------------------------------------------------------------------------------------------------------------------------------|
| Product remark | Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times. |
|----------------|----------------------------------------------------------------------------------------------------------------------------------|

## EQUIPMENT / ACCESSORIES

- Mounting bracket included
- Mounting screws and dowels included

- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

## DOWNLOAD DATA

| Documents and certificates                                                       |                                 |
|----------------------------------------------------------------------------------|---------------------------------|
|  | User instruction                |
|  | Declarations Of Conformity CE   |
|  | Declarations Of Conformity UKCA |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                 |
|---------------|------------------------------|--------------------------------------|--------------|------------------------|
| 4058075484511 | Folding box<br>1             | 95 mm x 1,237 mm x 335 mm            | 5489.00 g    | 39.37 dm <sup>3</sup>  |
| 4058075484528 | Shipping box<br>3            | 1,250 mm x 302 mm x 367 mm           | 18116.00 g   | 138.54 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

- Further information and frequently asked questions (FAQs) at [www.ledvance.com/consumer/smart/faq](http://www.ledvance.com/consumer/smart/faq)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.