

# PRODUCT DATASHEET SMART+ Wifi Orbis Spiral White 500mm TW

Spiral | Decorative ceiling luminaires with WiFi technology



# Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

## Product benefits

- Easy and quick installation

#### **Product features**

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Dimmable
- Network protocol: WiFi



# TECHNICAL DATA

## Electrical data

Nominal wattage	40.00 W	
Nominal voltage	220240 V	
Mains frequency	5060 Hz	
Nominal current	177.000 mA	
Power factor $\lambda$	> 0.50	
Total harmonic distortion	< 20 %	
Protection class	I	
Operating mode	Mains voltage	

# Photometrical data


Luminous flux	1900 lm	
Total luminous flux of contained light sources	4060 lm	
Luminous efficacy	102 lm/W	
Color temperature	30006500 K	
Reference control setting of contained light source (Kelvin)	3000 K <sup>1)</sup>	
Light color (designation)	Tunable White	
Color rendering index Ra	> 80	
Standard deviation of color matching	< 6 sdcm	
Photobiological safety group acc. to EN62778	RG1	
Photobiological safety group acc. to EN62471	RG1	
Beam angle	161.00 °	

<sup>1)</sup> Performing a reset will restore the default values set by the manufacturer

# Dimensions & Weight

Diameter	500.00 mm
Height	66.00 mm
Product weight	4000.00 g

TW



# Materials & Colors

Product color	White	
Housing color	White	
Body material	Polymethylmethacrylate (PMMA)	
Cover material	Polymethylmethacrylate (PMMA)	
Glow Wire Test according to IEC 60695-2-12	650 °C	
Mercury content	0.0 mg	

# **Application & Mounting**

Ambient temperature range	-20+40 °C
Type of connection	Screw terminal
Type of protection	IP20
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
LED module replaceable	Not replaceable
With light source	No

# Lifespan

TW

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

# Certificates & Standards

Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No

## Additional product data

Product remark  Reset settings to default by switching the product on for three second and repeating this five times.
---

## **EQUIPMENT / ACCESSORIES**

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

## DOWNLOAD DATA

	Documents and certificates
PDF	User instruction
PDF	Declarations Of Conformity CE

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075486607	Folding box 1	76 mm x 542 mm x 544 mm	4411.00 g	22.41 dm <sup>3</sup>
4058075486614	Shipping box	565 mm x 247 mm x 568 mm	14277.00 g	79.27 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.