

PRODUCT DATASHEET

TRUSYS FLEX P RAIL 600 8P END WT

TruSys® FLEX ENERGY RAIL 8-POLE | 8-pole mounting rail

Areas of application

- Industry halls, high rack warehouse, hardware stores



PERFOR-
MANCE
CLASS

Product benefits

- Simple installation
- High flexibility thanks to three available lengths (1500 mm, 3000 mm, 4500 mm and 1500 mm end rail)
- Version of 600 mm rail to be used with TRUSYS FLEX SENSOR TRACK

Product features

- Through wired with 8 core cable
- Different lengths available
- Electrical connection internal at the first luminaire, no external connection unit required
- Steel-sheet housing
- End-Rail without electrical and mechanical connectors




TECHNICAL DATA

Electrical data

Protection class	I
------------------	---

Dimensions & Weight

Length	600 mm
Width	70.2 mm
Height	38.8 mm
Product weight	580.00 g



Materials & Colors

Product color	White
Body material	Steel

Application & Mounting

Mounting location	Ceiling
With light source	No

Certificates & Standards

Standards	CE / CB / UKCA / ENEC / EAC
-----------	-----------------------------

Additional product data

Product remark	Available from March 2024
----------------	---------------------------

EQUIPMENT / ACCESSORIES

– Various accessories available

DOWNLOAD DATA

Documents and certificates	
	Declarations Of Conformity CE
	Declarations Of Conformity UKCA

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854193545	Sleeve 1	150 mm x 233 mm	597.00 g	
4099854193552	Shipping box 4	672 mm x 193 mm x 145 mm	2930.00 g	18.81 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.