

# PRODUCT DATASHEET

## LEDinestra 30CM 27 190° DIM 3W 927

### Frosted S14s

LEDinestra® DIM HD Lighting | Dimmable tubular LED lamps



#### Areas of application

- Ideal for mirror lighting
- Hotels, restaurants
- Domestic applications
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Very good color rendering ( $R_a \geq 90$ )
- Very long lifetime of up to 25,000 h
- Lower energy consumption than incandescent or halogen lamps

#### Product features

- LED alternative to tubular incandescent lamps
- Dimmable (with many common dimmers, see also [www.ledvance.com/dim](http://www.ledvance.com/dim))
- For especially uniform illumination




TECHNICAL DATA

Electrical data

|                                          |             |
|------------------------------------------|-------------|
| Nominal wattage                          | 3 W         |
| Construction wattage                     | 3.00 W      |
| Nominal voltage                          | 220...240 V |
| Operating mode                           | AC Mains    |
| Claimed equiv. conventional lamp power   | 27 W        |
| Nominal current                          | 16 mA       |
| Type of current                          | AC          |
| Inrush current                           | 0.29 A      |
| Operating frequency                      | 50/60 Hz    |
| Mains frequency                          | 50/60 Hz    |
| Max. lamp no. on circuit break. 10 A (B) | 500         |
| Max. lamp no. on circuit break. 16 A (B) | 800         |
| Total harmonic distortion                | ≤ 150 %     |
| Power factor λ                           | ≥ 0.40      |

Photometrical data

|                                         |            |
|-----------------------------------------|------------|
| Luminous flux                           | 275 lm     |
| Nominal useful luminous flux 90°        | 275 lm     |
| Luminous efficacy                       | 91 lm/W    |
| Lumen main.fact.at end of nom.life time | 0.96       |
| Light color (designation)               | Warm white |
| Color temperature                       | 2700 K     |
| Color rendering index Ra                | 90         |
| Light color                             | 927        |
| Standard deviation of color matching    | ≤6 sdcn    |
| Flickering metric (Pst LM)              | 1.0        |
| Stroboscope effect metric (SVM)         | 0.4        |



Light technical data

|                     |          |
|---------------------|----------|
| Beam angle          | 190 °    |
| Warm-up time (60 %) | < 0.50 s |
| Starting time       | < 0.5 s  |

Dimensions & Weight

|                  |           |
|------------------|-----------|
| Overall length   | 300.00 mm |
| Diameter         | 29.00 mm  |
| Maximum diameter | 29 mm     |
| Product weight   | 55.00 g   |

Temperatures & operating conditions

|                                      |              |
|--------------------------------------|--------------|
| Ambient temperature range            | -20...+40 °C |
| Maximum temperature at tc test point | 51.7 °C      |

Lifespan

|                                              |         |
|----------------------------------------------|---------|
| Lifespan L70/B50 at 25 °C                    | 25000 h |
| Number of switching cycles                   | 100000  |
| Lumen maintenance at end of service lifetime | 0.96    |

Additional product data

|                             |                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Base (standard designation) | S14s                                                                                                                                                                                                                                                                                                                                         |
| Mercury content             | 0.0 mg                                                                                                                                                                                                                                                                                                                                       |
| Mercury-free                | Yes                                                                                                                                                                                                                                                                                                                                          |
| Design / version            | Frosted                                                                                                                                                                                                                                                                                                                                      |
| Product remark              | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

Capabilities

|          |                   |
|----------|-------------------|
| Dimmable | Yes <sup>1)</sup> |
|----------|-------------------|

1) Check dimmer compatibility at [ledvance.com/compatibility](https://www.ledvance.com/compatibility)

Certificates & Standards

|                                              |                 |
|----------------------------------------------|-----------------|
| Energy efficiency class                      | F 1)            |
| Energy consumption                           | 3.00 kWh/1000h  |
| Type of protection                           | IP20            |
| Standards                                    | CE / UKCA / EAC |
| Photobiological safety group acc. to EN62778 | RG1             |

1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

|                 |                 |
|-----------------|-----------------|
| Order reference | LEDINES 30CM 3W |
|-----------------|-----------------|

LOGISTICAL DATA

|                              |              |
|------------------------------|--------------|
| Temperature range at storage | -20...+80 °C |
|------------------------------|--------------|

Energy labelling regulation data acc EU 2019/2015

|                                                     |              |
|-----------------------------------------------------|--------------|
| Lighting technology used                            | LED          |
| Non-directional or directional                      | NDLS         |
| Mains or non-mains                                  | MLS          |
| Light source cap-type (or other electric interface) | S14s         |
| Connected light source (CLS)                        | No           |
| Color-tuneable light source                         | No           |
| Envelope                                            | No           |
| High luminance light source                         | No           |
| Anti-glare shield                                   | No           |
| Correlated colour temperature type                  | SINGLE_VALUE |
| Standby power                                       | 0 W          |
| Claim of equivalent power                           | Yes          |
| Length                                              | 300.00 mm    |
| Height                                              | 29.00 mm     |
| Width                                               | 29.00 mm     |
| Chromaticity coordinate x                           | 0.458        |
| Chromaticity coordinate y                           | 0.410        |
| R9 Colour rendering index                           | 50           |

|                                                      |            |
|------------------------------------------------------|------------|
| Beam angle correspondence                            | SPHERE_360 |
| Survival factor                                      | 0.9        |
| Displacement factor                                  | 0.5        |
| LED light source replaces a fluorescent light source | No         |
| EPREL ID                                             | 1838198    |
| Model number                                         | AC57802    |

## DOWNLOAD DATA

| Documents and certificates                                                        |                                 |
|-----------------------------------------------------------------------------------|---------------------------------|
|   | Declarations Of Conformity CE   |
|   | Declarations Of Conformity UKCA |
| Photometric and lighting design files                                             |                                 |
|  | Spectral power distribution     |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4099854232831 | Folding box<br>1             | 32 mm x 50 mm x 342 mm               | 78.00 g      | 0.55 dm <sup>3</sup> |
| 4099854232848 | Shipping box<br>10           | 352 mm x 172 mm x 120 mm             | 941.00 g     | 7.27 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

- For dimming conformity see [www.ledvance.com/dim](http://www.ledvance.com/dim)
- For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.