

## PRODUCT DATASHEET

### HQI-T 2000 W/D

POWERSTAR HQI®-T 1000...2000 W | Metal halide lamps for enclosed luminaires



#### Areas of application

- Factories and workshops
- Sports halls and multi-purpose halls
- Industrial installations
- Airports
- Docks and port facilities
- Marshaling yards, container transshipment facilities
- Approved only for use in enclosed luminaires
- Outdoor applications only in suitable luminaires

#### Product benefits

- High efficiency
- E40 screw base for simple lamp handling
- UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter

#### Product features

- POWERSTAR® quartz technology
- Light colors: neutral white (N), daylight (D)



## TECHNICAL DATA

### Electrical data

|                                     |                                             |
|-------------------------------------|---------------------------------------------|
| Nominal wattage                     | 2000 W                                      |
| Nominal voltage                     | 230 V                                       |
| Ignition voltage                    | 4.0/5.0 kVp <sup>1)</sup>                   |
| Operating mode                      | Conventional control gear (CCG) and ignitor |
| Nominal current                     | 10.3 A                                      |
| PFC capacitor at 50 Hz              | 85 µF                                       |
| Rated lamp efficacy (HF data 25 °C) | 85 lm/W                                     |

<sup>1)</sup> Minimum / Maximum

### Photometrical data

|                                     |           |
|-------------------------------------|-----------|
| Luminous flux                       | 180000 lm |
| Luminous efficacy                   | 85 lm/W   |
| Color temperature                   | 7250 K    |
| Color rendering index Ra            | 80        |
| Light color                         | 872       |
| Rated lamp efficacy (HF data 25 °C) | 85 lm/W   |
| UV protection                       | Yes       |

### Dimensions & Weight

|                           |           |
|---------------------------|-----------|
| Overall length            | 430.00 mm |
| Length                    | 430.00 mm |
| Light center length (LCL) | 265,0 mm  |
| Diameter                  | 106.00 mm |
| Product weight            | 580.00 g  |

### Temperatures & operating conditions

|                                          |        |
|------------------------------------------|--------|
| Maximum permitted outer bulb temperature | 500 °C |
| Maximum permitted base edge temperature  | 250 °C |

### Lifespan

|              |        |
|--------------|--------|
| Lifespan B50 | 9000 h |
|--------------|--------|

### Additional product data

|                             |     |
|-----------------------------|-----|
| Base (standard designation) | E40 |
|-----------------------------|-----|

|                  |                          |
|------------------|--------------------------|
| Mercury content  | 170.0 mg                 |
| Design / version | Clear                    |
| Product remark   | Not for general lighting |

Capabilities

|                             |     |
|-----------------------------|-----|
| Dimmable                    | No  |
| Burning position            | p30 |
| Enclosed luminaire required | Yes |
| Hot restart                 | No  |

Country-specific categorizations

|                 |                                     |
|-----------------|-------------------------------------|
| ILCOS           | MT/UB-2000/972-E/E/SL-E40-106/430/H |
| Order reference | HQI-T 2000W/D E                     |

DOWNLOAD DATA

| Documents and certificates                                                         |                               |
|------------------------------------------------------------------------------------|-------------------------------|
|   | User instruction              |
|  | Declarations Of Conformity CE |
|  | Certificates                  |
| Photometric and lighting design files                                              |                               |
|  | Spectral power distribution   |

LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume    |
|---------------|------------------------------|--------------------------------------|--------------|-----------|
| 4008321526809 | Round wrap<br>1              | 465 mm x 130 mm x 130 mm             | 775.00 g     | 7.86 dm³  |
| 4008321526816 | Shipping box<br>4            | 275 mm x 270 mm x 525 mm             | 3724.00 g    | 38.98 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.