

# PRODUCT DATASHEET SPC.T OVEN CL 15 W 230 V E14

SPECIAL OVEN T | Incandescent lamps, tubular shape, for oven lighting



### Areas of application

- Domestic baking ovens

### **Product features**

- Ambient temperature: up to 300 °C




# TECHNICAL DATA

# Electrical data

Nominal wattage	15 W
Construction wattage	15.00 W
Nominal voltage	230 V

# Photometrical data

Luminous flux	85 lm
Luminous efficacy	5 lm/W
Lumen main.fact.at end of nom.life time	0.80
Color temperature	2700 K
Color rendering index Ra	100
Light color	1027



# Light technical data

	Starting time	0 s
_		

# Dimensions & Weight

Overall length	50.00 mm
Length with base excl. base pins/connection	50.00 mm
Light center length (LCL)	43,0 mm
Diameter	22,0 mm
Product weight	10.00 g

# Lifespan

ifespan L70/B50 at 25 °C	1000 h

# Additional product data

Base (standard designation)	E14		
Mercury-free	Yes		
Design / version	Clear		
Capabilities			
Dimmable	Yes		
Certificates & Standards			
Energy efficiency class	G		
Energy consumption	15.00 kWh/1000h		
Country-specific categorizations			
ILCOS	IBT/C-15-230-E14-22		
Order reference	SPC.T OVEN CL 1		
Energy labelling regulation data acc EU 2019/2015			
Energy labelling regulation data acc EU 2019/2015			
Energy labelling regulation data acc EU 2019/2015  Lighting technology used	OTHER		
	OTHER NDLS		
Lighting technology used			
Lighting technology used  Non-directional or directional	NDLS		
Lighting technology used  Non-directional or directional  Mains or non-mains	NDLS MLS		
Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)	NDLS MLS E14		
Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)	NDLS MLS E14 No		
Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source	NDLS MLS E14 No No		
Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope	NDLS MLS E14 No No No		
Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source	NDLS MLS E14 No No No No No		
Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source  Anti-glare shield	NDLS MLS E14 No No No No No No No		

No

50.00 mm

22,0 mm

22,0 mm

0.493

0.412

714477

AC35392

SPHERE\_360

Claim of equivalent power

Chromaticity coordinate x

Chromaticity coordinate y

Beam angle correspondence

Length

Height

Width

EPREL ID

Model number

### DOWNLOAD DATA

### Documents and certificates



Declarations Of Conformity CE

### Photometric and lighting design files



Spectral power distribution

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300003108	Folding box 1	68 mm x 28 mm x 29 mm	14.00 g	0.06 dm <sup>3</sup>
4050300554495	Bundle 10	176 mm x 71 mm x 218 mm	140.00 g	2.72 dm <sup>3</sup>
4050300554501	Shipping box 100	308 mm x 149 mm x 228 mm	1510.00 g	10.46 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.