

PRODUCT DATASHEET

Touch DIM LS/PD LI

Touch DIM® LS/PD LI | Light and presence sensors for light management systems



Areas of application

- Single luminaires in office areas

Product benefits

- A setpoint for daylight-dependent control can be stored by double clicking
- Operated via standard switches

Product features

- Touch DIM light and presence sensor
- Can also be operated purely as a presence sensor
- Maximum signal line length: 10 m
- Maximum power input: 0.5 W
- Delay time: 15 min

TECHNICAL DATA

Electrical data

Nominal wattage	0.50 W
Nominal voltage	220...240 V
Mains frequency	50 Hz

Dimensions & Weight

Length	63.00 mm
Width	29.00 mm
Height	21.00 mm
Product weight	24.00 g

Colors & materials

Product color	Anthracite
---------------	------------

Temperatures & operating conditions

Ambient temperature range	0...+50 °C
---------------------------	------------

Capabilities

Dimmable	No
Dimming interface	Touch DIM
Max. cable length to lamp/LED module	10 m
Number of control outputs	1
Maximum installation height	4 m
Detection angle	80 ° 1)
Type of installation	Luminaire integration
Operating range, light sensor	10...350 lx 2)

1) Approximately

2) Approximately, measured at the sensor

Certificates & Standards

Approval marks – approval	CE
Protection class	II
Type of protection	IP20

EQUIPMENT / ACCESSORIES

– Suitable for up to 4 QTi DALI ECG or 4 HTi DALI transformers or 4 OTi DALI LED drivers

DOWNLOAD DATA

Documents and certificates	
	User instruction
	Declarations Of Conformity CE
	Certificates
CAD/BIM files	
	CAD data 3D PDF

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321023025	Folding box 1	215 mm x 35 mm x 43 mm	57.57 g	0.32 dm ³
4008321023032	Shipping box 25	217 mm x 180 mm x 217 mm	1617.14 g	8.48 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.