

PRODUCT DATASHEET

Vintage 1906 PenduLum Triple Canopy Linear

Vintage 1906® PenduLum CANOPY | Canopy for 1906 PenduLum

Areas of application

- Living areas (living rooms, dining rooms, bedrooms etc.)
- Professional (hotels, bars, boutiques etc.)



Product benefits

- Ceiling mounting accessory to combine up to three PenduLum luminaires



TECHNICAL DATA

Electrical data

Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Protection class	I
Operating mode	Mains voltage

Dimensions & Weight

Length	540 mm
Width	50.0 mm
Height	50.0 mm
Product weight	676.00 g
Cable length	1,5 m

Materials & Colors

Product color	Black
Body material	Steel
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screwless terminal, 3-Pole
Type of protection	IP20
Dimmable	No

Additional product data

Product remark	Maximum bulb wattage: 3 x 12 W LED
----------------	------------------------------------

DOWNLOAD DATA

Documents and certificates



User instruction



Packaging insert



Declarations Of Conformity CE



Declarations Of Conformity UKCA

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854092831	Folding box 1	75 mm x 105 mm x 630 mm	891.00 g	4.96 dm ³
4099854092848	Shipping box 4	650 mm x 170 mm x 235 mm	4017.00 g	25.97 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– Further information at www.ledvance.com/consumer/products/product-stories/vintage-edition-1906

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.