

# PRODUCT DATASHEET Orbis Tray Sparkle Remote-CCT 580mm 35W

ORBIS® Tray Sparkle | LED Luminaire with sparkling effect and nickel ring



#### Areas of application

- For indoor use only
- Decorative domestic lighting
- Ceiling and wall surface mounting

## Product benefits

- Very homogenous light
- Easy and quick installation

#### **Product features**

- Ceiling luminaire with advanced LED technology
- Circular light emission
- Housing surface made of brushed nickel
- Color temperature adjustment, dimming and night functions via remote control



## **TECHNICAL DATA**

## Electrical data


Nominal wattage	35.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Power factor $\lambda$	> 0.90
Protection class	1

## Photometrical data

Luminous flux	2000 lm	
Luminous efficacy	57 lm/W	
Color temperature	27006500 K	
Light color (designation)	Warm White / Cool White / Daylight	
Color rendering index Ra	> 80	
Beam angle	120 °	

# Dimensions & Weight

Diameter	580.00 mm
Height	135.00 mm
Product weight	2200.00 g



## Materials & Colors

Product color	White	
Housing color	White	
Body material	Aluminum	
Cover material	Polymethylmethacrylate (PMMA)	
Mercury content	0.0 mg	

## **Application & Mounting**

Ambient temperature range	-20+40 °C
Type of connection	Screw terminal
Type of protection	IP20
Dimmable	Yes
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
LED module replaceable	Not replaceable
With light source	Yes

## Lifespan

Lifespan L70/B50 at 25 °C	25000 h <sup>1)</sup>
Number of switching cycles	100000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## **BATTERY**

Type of Battery	Alkaline	
Battery size [GMS]	AAA	
Nominal voltage of battery	1.5 V	

## Certificates & Standards

Standards	CE / REACH / RoHS
Luminaire with limited surface temperature, "D sign"	No

## **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included

## DOWNLOAD DATA

	Documents and certificates
PDF	User instruction
PDF	Packaging insert
PDF	Declarations Of Conformity CE

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075227545	Shipping box	160 mm x 600 mm x 600 mm	2858.00 g	57.60 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

35W