

PRODUCT DATASHEET Linear LED Flat Sensor 12W 3000K

LinearLED Flat® | Slim undercabinet luminaire for surface mounting

Areas of application

- Undercabinet lighting



Product benefits

- Connection of up to 43 (ECO version) or 18 (sensor Version) luminaires in a row
- Various accessories included: cables and connectors



TECHNICAL DATA

Electrical data

Nominal wattage	12.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	100.000 mA
Power factor λ	> 0.5
Protection class	II

Photometrical data

Luminous flux	760 lm
Total luminous flux of contained light sources	1230 lm
Luminous efficacy	63 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	≤6 sdcm
Photobiological safety group acc. to EN62778	RG0
Beam angle	120°

Dimensions & Weight

Length	527.00 mm
Width	67.00 mm
Height	19.00 mm
Product weight	425.00 g



Materials & Colors

Product color	Silver
Housing color	Silver
Body material	Aluminum

Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C
Type of connection	Plug type C (EU)
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Cabinet undersides
Application environment	Indoor
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Number of switching cycles 100000

Sensor

Type of sensor	Motion
Sensor technology	Passive infrared (PIR)

Certificates & Standards

Standards	CE / EAC
Luminaire with limited surface temperature, "D sign"	No

Additional product data

3.74

DOWNLOAD DATA

	Documents and certificates
POF	User instruction
POF	Packaging insert
PDF	Declarations Of Conformity CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075264410	Folding box 1	38 mm x 71 mm x 629 mm	447.00 g	1.70 dm ³
4058075264427	Shipping box 8	652 mm x 335 mm x 95 mm	4809.00 g	20.75 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.