

PRODUCT DATASHEET TRUSYS FLEX T5 TRACK ST WT

TruSys® FLEX T5 TRACK | Track rail insert for mounting of T5 LED tubes



Product benefits

- Simple installation

Product features

- 150 cm insert with T5 tube fitting holders and preinstalled wires
- Including optional side covers for luminaire inserts




TECHNICAL DATA

Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	I

Dimensions & Weight

Length	1498.5 mm
Width	77.70 mm
Height	91 mm
Product weight	1040.00 g



Materials & Colors

Product color	White
Housing color	White
Body material	Steel
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-25+40 °C	
Type of connection	Insulation displacement connector	
Type of protection IP20		
Protection class IK (shock resistance)	IKO4	
Mounting location	Mounting rail	
With light source	No	

Holder designation	G5

Lifespan

Lifespan L70/B50 at 25 °C	100000 h ¹⁾

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / CB / UKCA / ENEC / EAC
Ball shot safe	No

Additional product data

Product remark	Available from March 2024

DOWNLOAD DATA

	Documents and certificates
PDF	User instruction
PDF	Packaging insert
PDF	Declarations Of Conformity CE
POF	Declarations Of Conformity UKCA

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854230158	Folding box 1	128 mm x 1,539 mm x 135 mm	1548.00 g	26.59 dm ³
4099854230165	Shipping box 6	1,557 mm x 401 mm x 292 mm	11421.00 g	182.31 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.