

PRODUCTINFORMATIEBLAD DALI SENSOR LS/PD CI G2

DALI SENSOR LS/PD CI G2 | DALI-2 licht- en aanwezigheidssensor, plafondintegratie



Toepassingsgebieden

- Suitable for indoor applications
- Individual offices
- Open-plan offices
- Classrooms
- Conference rooms
- Corridors

Productvoordelen

- Flat design, very small structural height
- Simple and fast installation via wire springs
- DALI-2 certified
- DALI Bus powered (No mains connection necessary)
- Multiple sensors connectable to the same DALI line
- Presence detection angle adjustable between 40...90° via integrated shutters
- Integretable in light- and building management systems supporting DALI-2 sensors

Productkenmerken


- Light and presence sensor for ceiling integration
- Presence detection via passive IR element
- Light sensor operating range: 20...800 lx (measured at sensor)
- Mounting height: 2...5 m
- Function indicator with two-color LED
- Ceiling installation adapter

TECHNISCHE GEGEVENS

ELEKTRISCHE GEGEVENS

Nominale vermogen	0,10 W
Nominale spanning	16 V
Netfrequentie	0 Hz

AFMETINGEN & GEWICHT



Lengte	80,00 mm
Breedte	80,00 mm
Breedte (incl. ronde armaturen)	80.00 mm
Hoogte	55,00 mm ¹⁾
Hoogte (incl. cylin. armaturen)	55.00 mm
Diameter	80,0 mm
Product gewicht	95,00 g

1) h1

KLEUREN & MATERIALEN

Kleur van het product	Wit
-----------------------	-----

TEMPERATUREN & BEDRIJFSOMSTANDIGHEDEN

Omgevingstemperatuur bereik	-20...+50 °C
-----------------------------	--------------

MOGELIJKHEDEN

Dimbaar	Nee
Dimmer interface	DALI-2
Maximale inbouwhoogte	5 m
Detectie zone	6 m
Detectie hoek	40...90 °
Type montage	Verzonken
Bereik van de lichtsensor	20...800 lx

CERTIFICATEN & NORMEN

Keurmerken	CE
Veiligheidsklasse	II
Type bescherming	IP20

Technische uitrusting

- Suitable for many OSRAM DALI control systems

DOWNLOADS


Documenten en certificaten	Document name
 User instruction	DALI2 SENSOR LS/PD CI
 Declarations Of Conformity CE	DALI G2 CE 4202657 190320

LOGISTIEKE GEGEVENS

Productcode	Verpakkingseenheid (stuks per verpakking)	Afmetingen (lengte x breedte x hoogte)	Brutogewicht	Volume
4062172072083	BAG 1	128 mm x 37 mm x 27 mm	49.00 g	0.13 dm³
4062172072090	Verzenddoos 10	217 mm x 217 mm x 180 mm	1175.00 g	8.48 dm³

De genoemde productcodes beschrijven de kleinste hoeveelheid die besteld kan worden. Eén verzendeenheid kan bestaan uit één of meer afzonderlijke producten. Bij het plaatsen van een order enkele of veelvouden van de verpakkingseenheid invoeren.

AANVULLENDE CATALOGUSINFORMATIE



DISCLAIMER

Onder voorbehoud van verandering zonder kennisgeving. Fouten en drukfouten voorbehouden. Zorg ervoor dat u de meest recente versie gebruikt.