Data Sheet | Item Number: 774-9994/106-702


pre-assembled connecting cable; Eca; Socket/open-ended; 4-pole; Cod. A; H05VV-

F 4G 1.5 mm²; 7 m; 1,50 mm²; white

https://www.wago.com/774-9994/106-702







Dimensions in mm

Cable assembly WINSTA® RD rated current 16 A

The WINSTA® RD cable assembly rated current 16 A provides the foundation for installation of solid and fine-stranded conductors. The mechanical coding and color coding of the pluggable installation connector ensure error-free installation of the individual components – including protection against mismating. The pluggable installation connector is protected against ingress by solid objects in accordance with protection type IP20 (When mated: IP2xC (These compact connectors are not designed for use in open, easily accessible areas!)). The WINSTA® RD offers a round design that is perfect for use in conduits with an inner diameter of 20 mm, such as in construction of prefabricated houses. Of course, the safety of buildings must always be ensured, even after the electrical installation has been performed. The mandatory safety requirements in connection with EU CPR are fully satisfied by this product through fire class E.

Fast, error-free assembly thanks to cable assemblies from WAGO

The cable is pre-assembled with a socket and a free end. The WINSTA® Pluggable Connection System is perfectly tailored to the strict requirements of building installation. It makes electrical installation pluggable, and consequently faster, more reliable, and error-free. Using this pre-assembled system reduces assembly times and installation errors at the construction site. Now you can also lower installation expenses without compromising quality and safety: with fire class E reduces the need for servicing and prevents unnecessary downtime.

- pluggable installation connectors with protection against mismating
- products perfectly tailored to your requirements guarantee safe use
- suitable for any application
- custom-engineered solutions
- quick replacement of defective units during ongoing operation

Notes	
Note	Cables with a different fire class can be found in the eShop.

Electrical data					
Ratings per	IEC	/EN 60664	-1	General information	
Overvoltage category	III	III	II	Note on contact resistance	approx. 1 m Ω of contact resistance
Pollution degree	3	2	2		approx. $0.25\mathrm{m}\Omega$ contact transition plug/socket
Nominal voltage	250 V	-	-		5551.61
Rated surge voltage	4 kV	-	-		
Rated current	16 A	-	-		



Connection data			
Total number of potentials	4	Connection 1	
Conductor preparation ultrasonically tip-bonded	Strip length	9 mm / 0.35 inches	
	Pole number	4	
	Sheathed cable diameter	8.4 10.5 mm	
	Wire cross-section	1.5 mm ²	
	Strip length (outer insulation)	55 mm	
		Connection type	Socket - free end

Physical data		
Width	17.5 mm / 0.689 inches	
Height	17.5 mm / 0.689 inches	
Total length	7 m	

Mechanical data	
Application	General mains applications
Coding	A
Variable coding	No
Marking	N 21
Mating force of a plug-in connection	Approx. 30 70 N (depending on pole number)
Retention force of a plug-in connection	when locked: > 80N
Unmating force of a plug-in connection	Unlocked: approx. 30 70 N (depending on pole number)
Number of mating cycles	200, without resistive load
Connection type	Socket - free end
Type of pre-assembled cable	Connecting cable
Cable type	H05VV-F 4G1.5
Protection type	IP20; When mated: IP2xC (These compact connectors are not designed for use in open, easily accessible areas!)

Plug-in connection	
Mismating protection	Yes
Note on mismating protection	All WINSTA® components are 100% protected against mismating when: a.) plugging different numbers of poles b.) plugging while incorrectly rotated c.) plugging while laterally staggered
Locking lever	Yes
Locking of plug-in connection	Locking lever

Material data	
Note (material data)	Information on material specifications can be found here
Color	white
Insulation material	Polyamide (PA66)
Fire class per EN 50575	E _{ca}
Contact material	Copper or copper alloy; surface-treated
Contact plating	Tin
Fire load	209.413 MJ
Connector color	white
Strain relief color	white
Sheathed cable color	white
Printing color of sheathed cable	black
Halogen-free	No
Silicon-free	Yes

Data Sheet | Item Number: 774-9994/106-702

https://www.wago.com/774-9994/106-702



Material data	
Sheath material	PVC
Rubber cable	No
Weight	915.1 g
Copper weight of the pipe	0.058 kg/m

Environmental requirements	
Processing temperature	-5 +40 ℃
Continuous operating temperature	-35 +85 °C
Note on continuous operating temperature	Cable for temperatures ≤ 70 °C (including halogen-free) Insulating parts for temperatures ≤ 105 °C

Commercial data	
eCl@ss 10.0	27-44-06-04
eCl@ss 9.0	27-44-06-04
ETIM 8.0	EC002587
ETIM 7.0	EC002587
PU (SPU)	1 pcs
Packaging type	unpacked
Country of origin	DE
GTIN	4045454345938
Customs tariff number	85444290900

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Approvals / Certificates

General approvals

CCACCA CCA KEWA KEWA KEWA

Approval	Standard	Certificate Name
CCA DEKRA Certification B.V.	-	NTR NL 6374
CCA DEKRA Certification B.V.	EN 61535	NTR NL-7969
CCA DEKRA Certification B.V.	EN 61984	NTR NL-7848
KEMA/KEUR DEKRA Certification B.V.	EN 61535	71-123229
KEMA/KEUR DEKRA Certification B.V.	EN 61984	71-114944
KEMA/KEUR DEKRA Certification B.V.	-	2118353.01

Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
EU-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-
UK-Declaration of Conformity WAGO GmbH & Co. KG	-	-

Data Sheet | Item Number: 774-9994/106-702

https://www.wago.com/774-9994/106-702



Downloads Environmental Product Compliance Compliance Search Environmental Product Compliance 774-9994/106-702

Documentation			
Bid Text			
774-9994/106-702	19.02.2019	xml 3.02 KB	<u>↓</u>
774-9994/106-702	08.01.2015	doc 24.00 KB	$\underline{\downarrow}$

CAD/CAE-Data	
CAE data	
EPLAN Data Portal 774-9994/106-702	<u>↓</u>
WSCAD Universe 774-9994/106-702	$\overline{\downarrow}$

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

Page 4/4 Version 16.11.2023