


Data Sheet | Item Number: 294-5043

Lighting connector; push-button, external; without ground contact; 3-pole; Lighting side: for solid conductors; Inst. side: for all conductor types; max. 2.5 mm²; Surrounding air temperature: max 85°C (T85); 2,50 mm²; white

<https://www.wago.com/294-5043>



Color: white



Dimensions in mm

- External connection of solid, stranded and fine-stranded conductors
- Universal conductor termination (AWG, metric)
- Third contact located at the bottom of internal connection end
- Strain relief plate can be retrofitted

Electrical data									
Ratings per		IEC/EN 60998-1			Ratings per		IEC/EN 60998-2-2		
Overvoltage category		III	III	II	Overvoltage category		III	III	II
Pollution degree		3	2	2	Pollution degree		3	2	2
Nominal voltage		-	-	500 V	Nominal voltage		-	-	500 V
Rated surge voltage		-	-	4 kV	Rated surge voltage		-	-	4 kV
Rated current		-	-	24 A	Rated current		-	-	24 A

Connection data																																
Connection points	15	Connection 1 <table><tr><td>Connection type 1</td><td>External 1</td></tr><tr><td>Connection technology</td><td>Push-in CAGE CLAMP®</td></tr><tr><td>Number of connection points</td><td>2</td></tr><tr><td>Actuation type</td><td>Push-button</td></tr><tr><td>Connectable conductor materials</td><td>Copper</td></tr><tr><td>Solid conductor</td><td>0.5 ... 2.5 mm² / 18 ... 12 AWG</td></tr><tr><td>Solid conductor; push-in termination</td><td>0.5 ... 2.5 mm² / 18 ... 12 AWG</td></tr><tr><td>Stranded conductor</td><td>0.5 ... 2.5 mm² / 18 ... 14 AWG</td></tr><tr><td>Fine-stranded conductor</td><td>0.5 ... 2.5 mm² / 18 ... 14 AWG</td></tr><tr><td>Fine-stranded conductor; with insulated ferrule</td><td>0.5 ... 1.5 mm² / 18 ... 16 AWG</td></tr><tr><td>Fine-stranded conductor; with uninsulated ferrule</td><td>0.5 ... 1.5 mm² / 18 ... 16 AWG</td></tr><tr><td>Fine-stranded conductor; with ferrule; push-in termination</td><td>0.5 mm² / 18 AWG</td></tr><tr><td>Strip length</td><td>8 ... 9 mm / 0.31 ... 0.35 inches</td></tr><tr><td>Pole number</td><td>3</td></tr><tr><td>Wiring direction</td><td>Side-entry wiring</td></tr></table>	Connection type 1	External 1	Connection technology	Push-in CAGE CLAMP®	Number of connection points	2	Actuation type	Push-button	Connectable conductor materials	Copper	Solid conductor	0.5 ... 2.5 mm² / 18 ... 12 AWG	Solid conductor; push-in termination	0.5 ... 2.5 mm² / 18 ... 12 AWG	Stranded conductor	0.5 ... 2.5 mm² / 18 ... 14 AWG	Fine-stranded conductor	0.5 ... 2.5 mm² / 18 ... 14 AWG	Fine-stranded conductor; with insulated ferrule	0.5 ... 1.5 mm² / 18 ... 16 AWG	Fine-stranded conductor; with uninsulated ferrule	0.5 ... 1.5 mm² / 18 ... 16 AWG	Fine-stranded conductor; with ferrule; push-in termination	0.5 mm² / 18 AWG	Strip length	8 ... 9 mm / 0.31 ... 0.35 inches	Pole number	3	Wiring direction	Side-entry wiring
Connection type 1	External 1																															
Connection technology	Push-in CAGE CLAMP®																															
Number of connection points	2																															
Actuation type	Push-button																															
Connectable conductor materials	Copper																															
Solid conductor	0.5 ... 2.5 mm² / 18 ... 12 AWG																															
Solid conductor; push-in termination	0.5 ... 2.5 mm² / 18 ... 12 AWG																															
Stranded conductor	0.5 ... 2.5 mm² / 18 ... 14 AWG																															
Fine-stranded conductor	0.5 ... 2.5 mm² / 18 ... 14 AWG																															
Fine-stranded conductor; with insulated ferrule	0.5 ... 1.5 mm² / 18 ... 16 AWG																															
Fine-stranded conductor; with uninsulated ferrule	0.5 ... 1.5 mm² / 18 ... 16 AWG																															
Fine-stranded conductor; with ferrule; push-in termination	0.5 mm² / 18 AWG																															
Strip length	8 ... 9 mm / 0.31 ... 0.35 inches																															
Pole number	3																															
Wiring direction	Side-entry wiring																															
Total number of potentials	3																															
Number of connection types	4																															
PE function	without PE contact																															



Connection 2	
Connection type 2	Internal 2
Connection technology 2	PUSH WIRE®
Number of connection points 2	1
Actuation type 2	Push-in
Solid conductor 2	0.5 ... 2.5 mm² / 18 ... 14 AWG
Fine-stranded conductor; with insulated ferrule 2	0.5 ... 1 mm² / 18 ... 16 AWG
Fine-stranded conductor; with uninsulated ferrule 2	0.5 ... 1.5 mm² / 18 ... 14 AWG
Strip length 2	8 ... 9 mm / 0.31 ... 0.35 inches

Connection 4	
Connection type 4	Internal 4
Connection technology 4	PUSH WIRE®
Number of connection points 4	1
Actuation type 4	Push-in
Solid conductor 4	0.5 ... 0.75 mm² / 18 AWG
Strip length 4	8 ... 9 mm / 0.31 ... 0.35 inches

Connection 3	
Connection type 3	Internal 3
Connection technology 3	PUSH WIRE®
Number of connection points 3	1
Actuation type 3	Push-in
Solid conductor 3	0.5 ... 1.5 mm² / 18 ... 16 AWG
Fine-stranded conductor; with insulated ferrule 3	0.5 ... 0.75 mm² / 18 AWG
Fine-stranded conductor; with uninsulated ferrule 3	0.5 ... 1 mm² / 18 AWG
Strip length 3	8 ... 9 mm / 0.31 ... 0.35 inches

Physical data		
Pin spacing		10 mm / 0.394 inches
Width		30 mm / 1.181 inches
Height		21.53 mm / 0.848 inches
Height from the surface		17 mm / 0.669 inches
Depth		27.3 mm / 1.075 inches

Mechanical data	
Marking	3-2-1
Mounting type	Snap-in foot

Material data	
Note (material data)	Information on material specifications can be found here
Color	white
Material group	IIIa
Insulation material	Polycarbonate (PC)
Flammability class per UL94	V0
Clamping spring material	Chrome-nickel spring steel (CrNi)
Contact material	Electrolytic copper (E _{Cu})
Contact plating	Tin
Fire load	0.183 MJ
Halogen-free	Yes
Weight	9.2 g



Environmental requirements	
Temperature stability	120 °C
T marking	T85
Commercial data	
Product Group	8 (Misc. Chassis Mount Blocks)
eCl@ss 10.0	27-14-11-06
eCl@ss 9.0	27-14-11-06
ETIM 8.0	EC001284
ETIM 7.0	EC001284
PU (SPU)	500 pcs
Packaging type	Foil
Country of origin	CH
GTIN	4050821098256
Customs tariff number	85369010000
Environmental Product Compliance	
CAS-No.	131651-65-5 144317-44-2 220133-51-7 220689-12-3 25628-08-4 29420-49-3 375-73-5 503155-89-3 507453-86-3 68259-10-9
REACH Candidate List Substance	Perfluorobutane sulfonic acid (PFBS) and its salts
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c) 7(a) 7(c)-I 7(c)-II
SCIP notification number (Austria)	bf441729-d970-4de5-9592-524d141c28cd
SCIP notification number (Belgium)	800a7da9-8cf7-4139-8ac6-734f156a96d7
SCIP notification number (Bulgaria)	734ce1e5-521e-43ec-8326-e9505936ef8b
SCIP notification number (Czech Republic)	4fc31356-cf11-4609-a4c7-7495bd5ea98a
SCIP notification number (Denmark)	f810b911-5c32-45dd-bb49-741cc0bda46e
SCIP notification number (Finland)	22b5c839-9e89-4951-92c5-534338ae7795
SCIP notification number (France)	e1c1f934-253a-42f5-a545-d96e04966e9a
SCIP notification number (Germany)	c610f0a2-44d8-4821-8afa-27225325f408
SCIP notification number (Hungary)	525672d0-0192-4860-8237-f6e74d7406dd
SCIP notification number (Italy)	fe3f4312-e10b-4088-950d-9e36beae4a7
SCIP notification number (Netherlands)	6eacef25-13cd-4c75-a6d5-af3c10c2acf1
SCIP notification number (Poland)	f532beb7-5f57-4c9c-8940-98d127f1efbd
SCIP notification number (Romania)	2d6d1d0e-0969-4f6e-8d40-8a7835b4fff5
SCIP notification number (Sweden)	9577212c-826e-47c9-9344-eda5547928ae



Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
ENEC 05 DEKRA Certification B.V.	EN 60998	2128791.01

Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
EU-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-
UK-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-

Downloads

Environmental Product Compliance

Compliance Search
Environmental Product Compliance 294-5043



Documentation

Additional Information
Technical Section
pdf 2240.62 KB



Bid Text
294-5043
19.02.2019
xml 5.57 KB
294-5043
13.06.2017
doc 27.00 KB



CAD/CAE-Data

CAD data
2D/3D Models 294-5043



CAE data
WSCAD Universe 294-5043
ZUKEN Portal 294-5043



1 Compatible Products

1.1 Optional Accessories

1.1.1 Strain relief

1.1.1.1 Strain relief



[Item No.: 294-370](#)
Strain relief; for 294 Series; with snap-in
mounting feet; white

[Item No.: 294-375](#)
Strain relief; for 294 Series; without snap-
in mounting feet; white

1.1.1.2 Strain relief plate



Item No.: 294-364
Strain relief plate; for 294 Series; for multi-core cables; 3- to 5-pole; with secured clamp; white

Item No.: 294-384
Strain relief plate; for 294 Series; for single strands; 3- to 5-pole; with secured clamp; white

1.1.2 Tool




1.1.2.2 Operating tool



Item No.: 206-294
Disconnection tool; green

Installation Notes

Installation




3-pole – without ground contact

Snap-in foot


Drilled hole for snap-in mounting foot

Conductor termination




EUROPE
1 x 0.5 ... 2.5 mm ² "s"
1 x 0.5 ... 1.5 mm ² "s"
1 x 0.5 ... 0.75 mm ² "s"
AMERICA
1 x AWG 18 ... 14 "s"
1 x AWG 18 ... 16 "s"
1 x AWG 18 "s"
JAPAN
1 x 0.8 ... 1.6 mm diam. "s"
1 x 0.8 ... 1 mm diam. "s"
1 x 0.8 mm diam. "s"

EUROPE
2 x 0.5 ... 2.5 mm ² "s, str, f-str"
AMERICA
2 x AWG 18 ... 12 "s"
2 x AWG 18 ... 14 "s, f-str"
JAPAN
2 x 0.8 ... 2 mm diam. "s"
2 x 0.5 ... 2 mm ² "str, f-str"



Internal connection:
PUSH WIRE® for internal wiring with solid conductors

External connection:
Push-in CAGE CLAMP® for field-wiring with all conductor types



Terminating five conductors per pole – solid and fine-stranded.

