



Color: ■ gray

Electrical data

Ratings per IEC/EN	
Rated current	125 A

Physical data

Jumper assignment	1-2
-------------------	-----

Material data

Note (material data)	Information on material specifications can be found here
Color	gray
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.05 MJ
Weight	13.6 g

Commercial data



eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-14-11-40
ETIM 8.0	EC000489
ETIM 7.0	EC000489
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	IN
GTIN	4045454074524
Customs tariff number	85366990990

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 284-412	↓

Documentation			
Additional Information		Bid Text	
Technical Section	pdf 2240.62 KB	284-412	19.02.2019 xml 2.58 KB
	↓	284-412	19.09.2017 doc 22.50 KB
			↓

CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 284-412	EPLAN Data Portal 284-412
↓	↓
	WSCAD Universe 284-412
	↓
	ZUKEN Portal 284-412
	↓

Installation Notes	
Commoning	
	
Commoning with comb-style jumper bar. Individual arrangement: 125 A Two jumpers combined in one clamping unit: 100 A	Connecting 35 mm² (2 AWG) conductors to commoned terminal blocks. Screw clamp connection, side-entry wiring