



Color: ■ white

Cover WINSTA® MINI 4-pole

When using the cover from the WINSTA® MINI product line, zero-defect electrical installation is guaranteed. You can rely on the quality of WINSTA® components from WAGO for your electrical installation accessories too. Due to its particularly small dimensions, our WINSTA® MINI Pluggable Connection System with Push-in CAGE CLAMP® spring pressure connection technology is especially suitable in very restricted spaces, i.e., for connections when very little room is available.

Push-in CAGE CLAMP® spring pressure connection technology – pluggable installation instead of laborious screw connections!

The WINSTA® Pluggable Connection System is ideally tailored to the very strict requirements of building installation. It makes electrical installation pluggable, and thus more efficient, even more reliable, and error-free. Using this pre-assembled system decreases time spent on assembly and installation errors at the construction site. Choose quality and durability – the WINSTA® MINI accessory with protection against mismatching from WAGO makes the installation of electrical components visibly easier.

- consistent IP40 protection
- convenient installation and commissioning

| Connection data |   |
|-----------------|---|
| Connection 1    |   |
| Pole number     | 4 |

| Mechanical data |                |
|-----------------|----------------|
| Mounting type   | Snap-in flange |
| Suitable        | for cutout     |

| Material data               |                                                                                                                        |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------|
| Note (material data)        | <a href="https://www.wago.com/us/material-specifications">Information on material specifications can be found here</a> |
| Color                       | white                                                                                                                  |
| Insulation material         | Polyamide (PA66)                                                                                                       |
| Flammability class per UL94 | V0                                                                                                                     |
| Fire load                   | 0.045 MJ                                                                                                               |
| Weight                      | 1.5 g                                                                                                                  |



| Environmental requirements               |                                            |
|------------------------------------------|--------------------------------------------|
| Processing temperature                   | -5 ... +40 °C                              |
| Continuous operating temperature         | -35 ... +85 °C                             |
| Note on continuous operating temperature | Insulating parts for temperatures ≤ 105 °C |

| Commercial data       |               |
|-----------------------|---------------|
| Product Group         | 20 (Winsta)   |
| eCl@ss 10.0           | 27-44-06-92   |
| eCl@ss 9.0            | 27-44-06-92   |
| ETIM 8.0              | EC002863      |
| ETIM 7.0              | EC002863      |
| PU (SPU)              | 100 pcs       |
| Packaging type        | Box           |
| Country of origin     | DE            |
| GTIN                  | 4050821684329 |
| Customs tariff number | 39269097900   |

| Environmental Product Compliance |                        |
|----------------------------------|------------------------|
| RoHS Compliance Status           | Compliant,No Exemption |

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 890-694

↓

| Documentation |            |                 |   |
|---------------|------------|-----------------|---|
| Bid Text      |            |                 |   |
| 890-694       | 19.02.2019 | xml<br>2.59 KB  | ↓ |
| 890-694       | 11.03.2015 | doc<br>22.50 KB | ↓ |

| CAD/CAE-Data           |   |
|------------------------|---|
| CAE data               |   |
| WSCAD Universe 890-694 | ↓ |