

Double socket outlet vertical with pin earthing and shutters, flush-mounting depth 24 mm, complete device incl. faceplate, cream

100-67700

4 year warranty

Double flush-mounted socket outlet 16 A/250 Vac with pin earthing and shutters for vertical installation with flush-mounting depth 24 mm. The faceplate is attached to the socket outlet with screws. Complete device incl. faceplate and pre-assembled finishing set, Finishing colour: cream

Technical data

Double socket outlet vertical with pin earthing and shutters, flush-mounting depth 24 mm, complete device incl. faceplate, cream

- Colour: cream (coloured in mass, approximately NCS S 1005 - Y10R, RAL 1013)
- Type of earthing: pin earthing
- Power: 16 A/250 Vac
- Flush-mounting frame
 - 1 mm-thick metal
 - galvanized on all sides
 - with 4 grooves
- Material faceplate: The central plate is made of impact-resistant, dustproof and rigid polycarbonate. The base material is coloured in mass.
- Material earthing: solid brass nickel-plated pin earthing
- Fixing method
 - with screws for simple fixing in a flush-mounting box with grip surfaces
- Wire connection
 - the sockets are equipped with screw terminals for clamping the wires.
- Wire capacity
 - all connection terminals at the top side of the base
 - up to 4 x 2.5 mm² wire per terminal
- Earthing wire capacity
 - 2 x 2.5 mm² + 2 x 4 mm² wire in the earthing terminal
- – All plastic components are self-extinguishing (comply with a filament test of 650°C) and are halogen-free.
- Protection degree: IP20
- Protection degree: The combination of a mechanism, a central plate and a faceplate has a protection degree of IP21-D
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Certification marks: CEBEC, NF
- Marking: CE



$\frac{16 \text{ A}}{250 \text{ Vac}}$



niko

Wiring diagram

