

# Double 2-pole socket outlet without earthing, complete device incl. faceplate, white

101-67410

4 year warranty

Double 2-pole flush-mounting socket outlet, 16 A/250 Vac, with faceplate. The double socket outlet fits in 1 single flush-mounting box. The faceplate is attached to the socket outlet with screws. Complete device incl. faceplate and pre-assembled finishing set, Finishing colour: white

## Technical data

Double 2-pole socket outlet without earthing, complete device incl. faceplate, white

- Colour: white (coloured in mass, approximately NCS S 0502 - Y50R, RAL 9010)
- Type of earthing: without earthing
- Power: 16 A/250 Vac
- Flush-mounting frame
  - 1 mm-thick metal
  - galvanized on all sides
  - with 4 grooves
- Material faceplate: The central plate is made of impact-resistant, dustproof and rigid polycarbonate. The base material is coloured in mass.
- Fixing method
  - with screws for simple fixing in a flush-mounting box with grip surfaces
- Wire connection
  - the sockets are equipped with screw terminals for clamping the wires.
- Wire capacity
  - all connection terminals at the top side of the base
  - up to 4 x 2.5 mm<sup>2</sup> wire per terminal
- – All plastic components are self-extinguishing (comply with a filament test of 650°C) and are halogen-free.
- Protection degree: IP20
- Protection degree: The combination of a mechanism, a central plate and a faceplate has a protection degree of IP20.
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Marking: CE



$\frac{16 \text{ A}}{250 \text{ Vac}}$



**niko**

## Wiring diagram

